Vehicle Standards Bulletin No 14

National Code of Practice for Light Vehicle Construction and Modification

ICV MOTOR VEHICLE CHECKLIST (ADR Category MA, MB AND MC)

CODE LO1
CHECKLIST LO1-3

VERSION 2.0 JANUARY 2011

VIN	Certificate N°		Signature	
Signatory's Signature			<u>Date</u>	
Signatory Employer (if applicable)				
Vehicle Certified By (Signatory)				
Signatory Certification				
comply with	Output		KW or	BHP
ADR Engine was designed to	Maximum Power			
Displacement	Litres or	Cubic Inches	Year of Manufacture	
Make	Туре		Cylinders/Roto	ors
Engine Details			No. of	
Number			1 1 1	
VIN/Chassis Number				
Vehicle Mass (kg)	Fuel Tank Certifica Number (where app			
Make	Model		Year of Manufacture	
Vehicle Details			Voor of	
Email				
Telephone		Mobile		
Address				
Owner's Name				

MAKE:	ENGI	NE No.							ADR	Catego	ory						
MODEL		1						VIN:									
	•			REVE						•	•				•		
			ective ATURI	date for	MA ve	ehicles	July	1988)				1		omn	liance		
		r c <i>i</i>	HIUKI	<u>L</u>									(Julih	llalice	;	
Reversing light or lights fitted switched on?	and operate	e contin	uously	y only v	vhen re	everse	gear	selec	ted a	and igr	nition	Υ [] N	N \square	l NA		
Colour white/amber?								γ [_V	l na						
Number of lamps one/two (circ	le)?							Com	nlion	ما دارس	. rulo	-	_	_	ı	_	
		ADD	2/00 [DOOR	I ATCL	IEG V			-	ce with	1 ruie	YL	<u> </u>		NA	Ц	
				date for													
			ATURI				,						(Comp	liance	<u>)</u>	
Two (fully latched and seconda	•											Υ [l NA		
Locks on all side doors and op				interio	r?							γ [<u> </u>	<u> </u>	l NA		
Do front door locks prevent the	ir opening f	rom out	tside?									Υ [<u> </u>	<u> </u>	NA		
Rear Door Locks MA only Do the rear deer locks prevent	thoir oponir	na from	incido	and or	ıtcido2	or						YL	_ \	ıЦ	l NA	Ц	
Do the rear door locks prevent their opening from inside and outside? or Rear door locks prevent opening from outside and, inside by engagement of 'Child Safety Locks?'						у [<u> </u>	ıП	l _{NA}	П							
	<u> </u>		<u> </u>							ce with		y [<u> </u>	=	NA		
		ADR 3/														_	
			ective ATURI	date for	MA ve	ehicles	July	1988)				1		Comp	lionos		
Self-locking restraining device	and release				all hind	ned se	ats or	seat	back	s?		y [$\frac{1}{\sqrt{1}}$	л П	liance NA	<u> </u>	
Where seat must hinge or fold control readily accessible to the	to permit a	ccess t	o or e	gress f	rom ar	other					ease		<u> </u>		l _{NA}		
					,			Com	plian	ce with	rule	Y [v \square	l NA		
				and A date for													-
		FE/	ATURI	E									(Comp	liance	,	
Are seat belts fitted?												Υ [] N	۷ 	l NA		
Are they ADR compliant												y [v \square	l na		
Are newly installed seat belts r	iew?											Υ [v \square	l _{NA}		
If an alternate standard, are the	ey an equiv	alent Al	DR sta	ndard (eg RA	WS G	uidelin	es)?				Y [۷ <u> </u>	l NA		
All seat belts in good working o	ondition?											Y [] N	ا ا	l na		
VIN		Cer	tifica	ite N°					Sia	natur	-Δ						

ICV MA, MB and MC Vehicles - Checklist LO1-3 Retractor lap sash seat belts on all outboard seating positions for year of manufacture (except second row MC vehicle category, vehicles with no permanent structure and third row folding seats in cargo Y \square N \square NA \square area)?. (Note outboard positions without retractors) Lap belts, at least, for all other seating positions? Y \square N \square NA \square $Y \square N \square NA \square$ For swivelling seats is a seatbelt assembly provided for all positions in which the seat may be locked? Is there a durable label with the words 'WARNING THIS SEAT IS ONLY TO BE USED IN THE (FORWARD/REARWARD etc as applicable) FACING POSITION WHILST THE VEHICLE IS IN MOTION' affixed adjacent to the swivelling seat and visible to the person occupying that seat, and is a Y \square N \square NA \square seat belt provided for the forward and rearward facing positions? For any two seating position, identify: (1) location (2) mfr name/trade mark # (3) date of manufacture M/Y (4) identification code # (5) AS2596 Lic no Buckle Identification code if different to Lap/Sash If `E' marked R16, Approval No Driver's seatbelt incorporates an ELR? Y \square N \square NA \square All other outboard seatbelts incorporate an ELR and/or an ALALR? Y \square N \square NA \square For drivers seating position, the seat belt appears to 'Correctly Fit' a '95th Percentile Adult Male with Y \Box the seat in the foremost driving position, and a '5th Percentile Adult Female', with the seat in the rearmost driving position. For all other seating positions, the seat belt appears to 'Correctly Fit' a 95th Percentile Adult Male' with Y D N D NA D the seat in the foremost riding position, and a '50th Percentile 6 Year Old Child' with the seat in the rearmost riding position. All buckles of a quick-release design? $Y \square N \square NA \square$ Are release instructions printed legibly on the front of the buckle and/or the release coloured red or Y \square N \square NA \square orange? (ECE) Any free end of strap of a seatbelt, (1) Prevented from passing through an adjuster? Y \square N \square NA \square (2) Have at least 25mm available grip when fully extended? $Y \square N \square NA \square$ For 'Outboard Seating Positions' adjacent to a door, (3) Restrained against another strap? Y N N NA Buckle component of the retracting strap accessible? Y \square N \square NA \square Y \square N \square NA \square Buckle component of the non-retracting part of seatbelt accessible and (for individual front seats buckle component is rigid)? Positive feature to restrain outboard buckles? Y \square N \square NA \square Compliance with rule Y \square N \square NA \square ADR 5/03 - ANCHORAGES FOR SEATBELTS (Effective date for MA vehicles July 1988)

FEATURE	COMPLIANCE
	Y N N NA
All outboard seating positions include an upper anchorage (except second row MC vehicle category, vehicles with no permanent structure and third row folding seats in cargo area)?	Y N NA NA

VIN	Certificate N°	Signature
Notes:		

Lap anchor points on opposite sides of 'Seating Reference Plane'; minimum separation at least 165 $Y \square N \square NA \square$ Y \Box N \Box NA \Box Compliance with rule ADR 6/00 - DIRECTION INDICATOR LAMPS (Effective date for MA vehicles July 1988) Y \square N \square NA \square Direction turn signal lamps, front, rear and side fitted? Y \square N \square NA \square Colour amber? Y N N NA N Visibility 45° inboard and 80° outboard front and rear? Y \Boxed N \Boxed NA \Boxed Rear mounted tyre carrier complies with item 3 requirements (MC & MB vehicles only)? Y \square N \square NA \square Side repeater has rearwards visibility from 50 to 600 outboard? Distance between side indicator and front of vehicle does not exceed 1800 mm (or 2500 mm if Y \square N \square NA \square structure renders lower figure impossible)? Y \square N \square NA \square Compliance with rule **ADR 7/00 - HYDRAULIC BRAKE HOSES** (Effective date for MA vehicles July 1988) Hydraulic brake hoses that comply with ADR 42 need not comply with this rule COMPLIANCE **FEATURE** Y \square N \square NA \square Hydraulic brake hoses comply with SAE J1401, FMVSS 106 (Circle)? For any one brake hose, identify (1) Location?.... (2) Marking? Y \square N \square NA \square All brake hoses in a good condition and not perished or damaged? Compliance with rule Y \square N \square NA **ADR 8/00 - SAFETY GLAZING MATERIAL** (Effective date for MA vehicles July 1988) **FEATURE** COMPLIANCE All glazing suitably marked? Y \square N \square NA \square Windscreen glass marked as being laminated? Y \square N \square NA \square Glazing standard and approval No..... Windscreen marking Driver's side window marking..... Rear window marking..... Do surface tinted windows meet minimum 35% light transmittance and maximum 10% reflectance $Y \square N \square NA \square$ values (visual assessment)? Y N N NA N Compliance with rule Certificate N° VIN Signature

ADR 10/01 - STEERING COLUMN	
(Effective date for MA vehicles July 1988)	
FEATURE	COMPLIANCE
Steering column appears to have collapsible element?	Y N N NA
Compliance with rule	Y N N NA
ADR 11/00 – INTERNAL SUN VISORS	
(Effective date for MA vehicles July 1988)	00115111105
FEATURE	COMPLIANCE
Sun visors padded with energy absorbtion material?	Y U N U NA U
No rigid material edges less than 3 mm radius?? Compliance with rule	Y H N H NA H
·	Y LI N LI NA LI
ADR 12/00 - GLARE REDUCTION IN THE FIELD OF VIEW (Effective date for MA vehicles July 1988)	
FEATURE	COMPLIANCE
Are All Surfaces Of The Following Items Dull Metal Or Non-Metallic;	
(1) windscreen wiper arms and blades	y 🗆 n 🗖 na 🗖
(2) internal windscreen mouldings	y O N O NA O
(3) horn ring and hub of steering wheel	Y D N D NA D
(4) internal rear vision mirror frame and mounting bracket: and	y 🗆 n 🗆 na 🗖
(5) steering column mounted control levers and gear selectors quadrants.	y \square N \square NA \square
Compliance with rule	Y O N O NA O
ADR 13/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES	<u> </u>
(Effective date for MA vehicles July 1988)	
NOTE These inspection items are based on the latest issue of ADR 13/00. Vehicles may be certified to profit 13/00 that were in force at the time the vehicle was originally built.	evious versions of ADR
(1) All lamps constituting a pair must be symmetrical about the centre line of the vehicle.	
 (2) All forward and rearward facing lamps must be visible through 45° inboard and XX outboard without ob (3) Lamps must be undamaged and lenses untinted, uncracked and not excessively faded. 	ostruction.
Main beam headlamps	Y N N NA
Dipped beam headlamps	Y N N NA
Front fog lamp(s) (optional)	Y N N NA N
Reversing lamp(s)	Y N N NA N
	Y
Hazard warning lamps	Y N N NA NA NA
	Y N N NA N
Cornering lamps (optional)	
	Y N N NA
Stop (brake) lamps	Y
Stop (brake) lamps	

ADR 14/00 - REAR VISION MIRROR (Effective date for MA vehicles July 1988) COMPLIANCE **FEATURE** Reflective surface of RHS mirror flat? Y \square N \square NA \square May be convex **only if `E' marked** , Approval No Y \square N \square NA \square Reflective surface of internal mirror flat? If LHS external mirror fitted, is it 'Flat' or 'Convex'? (circle one). Y \square N \square NA \square RHS external mirror adjustable from the drivers seating position? Y O N O NA O RHS external mirror not obscured by the unwiped portion of the windscreen? Compliance with rule Y N N NA N **ADR 15/00 - DEMISTING OF WINDSCREEN** (Effective date for MA vehicles July 1988) COMPLIANCE **FEATURE** Y \square N \square NA \square Provision made for windscreen demisting? Y O N O NA O Compliance with rule ADR 16/00 - WINDSCREEN WIPERS & WASHERS (Effective date for MA vehicles July 1988) COMPLIANCE **FEATURE** Y \square N \square NA \square Corresponding areas wiped in front of the driver and the front seat passenger? Wiper and washer controls readily accessible to driver? Y \square N \square NA \square Number of frequencies? (including intermittent cycles) Windscreen washing system operational and serviceable? Y \square N \square NA \square Windscreen washing system reservoir capacity at least 1 litre? Y \square N \square NA \square Y \square N \square NA \square Compliance with rule **ADR 18/00 - INSTRUMENTATION** (Effective date for MA vehicles July 1988) COMPLIANCE **FEATURE** Speedometer on driver's side and all visual indicators readily visible by the driver? Y \square N \square NA \square Speed indicating element colour and background contrast? Y \square N \square NA \square All essential gauges and indicators other than warning lamps provided with variable intensity Y \square N \square NA \square illumination? Y \square N \square NA \square Vehicle speed indicated in Km/h only? If 'NO' is Major Scale Km/h? Y \square N \square NA \square Speedometer readily visible to the driver? Y \square N \square NA \square Odometer, Distance travelled indicated in a least 1Km units least from 1 to 600 000 Km Y \square N \square NA \square Y 🔲 N 🔲 NA 🛭 Compliance with rule VIN Certificate N° Signature

ADR 21/00 - INSTRUMENT PANEL

(Effective date for MA vehicles July 1988)

Notes:						
VIN	Certificate N°	Signature	9			
MAN	0 40 40	Τ	-			
Tyres fitted comply with DOT or E m	nark specifications?		Y			
At least 4 tread wear indicators?	and a series of the series of		Y O N O NA O			
(4) Regulation and marks	DOT					
(3) Date code	Fr Rr					
(2) Tyre size, speed category and carcass construction symbols	Fr Rr					
(1) Manufacturer or trade mar	k Fr Rr					
Are NEW tyres fitted? For one tyre fitted, identify: (If tyre si	ze different front and rear, con	nplete for 1 Fr & 1 Rr tyre)	Y N N NA			
Aro NEW turco fixed 2	FEATURE		COMPLIANCE			
	(Effective date for Ma	A vehicles July 1988)				
	ADR 24/00 - TYRE A	ND RIM SELECTION				
	C =					
	A = B =	В	B =			
			A =			
<u> </u>	IF HEAD RESTRAINT NON-	-SOLID, GIVE DIMENSIONS				
microcolori or scal cusmon and sca	t back at contro line of scat:	Compliance with	rule Y N N NA N			
Width not less than 170 mm for indivintersection of seat cushion and sea		nch seat at approx 700mm above	y □ N □ NA □			
Minimum height of upper boundary a seat greater than 700mm?.	above intersection of seat cush	nion and seat back at centre line c	of Y N N NA N			
Distance between upper and lower e	edges not less than 115 mm?		Y N N NA			
Head restraints fitted to front outboa	Y N N NA D					
	(Effective date for M. FEATURE	A vehicles July 1988)	COMPLIANCE			
		AD RESTRAINTS	rule Y N NA NA			
micror compartment door latenes of	Compliance with ru					
Area of instrument panel left of steel Interior compartment door latches of		actorily padded?	Y O N O NA O			
	FEATURE		COMPLIANCE			

-	1 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	J.3att	
VIN	Certificate N°	Signati	ure
		Compliance wit	ITTUE TO N LINA LI
Engine shioke of fuel/all fallo lest	conducted (test report attached)?	Compliance wit	
			Y O N O NA O
Engine filters, oils and injectors se			Y D N D NA D
	(Effective date for MA vehicle FEATURE	es July 1988)	COMPLIANCE
AD	R 30/00 - SMOKE EMISSION CONTRO		CLES
		Compliance wit	hrule Y N N NA N
Side doors have had impact intrus by appearance, comparison or tes	on bars fitted for occupant protection and? (Circle method)	d bars meet ADR stan	dards Y N N NA NA
Side doors fitted with OEM side in			Y O N O NA O
	(Effective date for MA vehicle		
	ADR 29/00 - SIDE DOOR S		
Stationary sound level measureme	nt (dBA)	Compliance wit]
	ood condition with no leaks or corrosion		Y D N D NA D
	satisfies WA VSR 2002 level for year of		Y O N O NA O
	FEATURE		COMPLIANCE
	(Effective date for MA vehicle		
	ADR 28/00 - EXTERNAL NOISE OF	· · · · · · · · · · · · · · · · · · ·	ITTUIC Y LA IV LA IVA LA
key removal activates the 'anti-the	t device, more than 2mm of movement r	equired to activate.? Compliance wit	Y LIN LINA LI
'Engine off' position to 'anti-theft' p	osition by more than a single rotary or lin	ear motion of the key,	or if Y N N NA N
With key in anti-theft position, is or	e of the following impossible? e gears/Release a brake? (Circle which i:	s annlicable)	y \square N \square NA \square
Key removal possible only in the a	<u>`</u>		y \square N \square NA \square
Switch position 'Engine On' to 'Ant	i-theft' through 'Engine Off'?		y \square N \square NA \square
	FEATURE		COMPLIANCE
	ADR 25/00 - ANTI-THEF (Effective date for MA vehicle		
		Compliance wit	hrule Y N N NA N
Rims marked according to ADR?			Y O N O NA O
Maximum load rating and speed co	ategory of tyre fitted equal to or greater the	nan that on the placard	d? Y N N NA N
All tyres fitted to the vehicle of the	same type of 'Carcass' construction?		Y 🗆 N 🗖 NA 🗀
(3) Statement on load rating and	speed category?		Y D N D NA D
(2) Recommended tyre pressure			Y D N D NA D

ADR 31/00 - PASSENGER CAR BRAKES (MA Category Only)

(Effective date for MA vehicles July 1988)

(Effective date for two verticles study 1700)	T
FEATURE	COMPLIANCE
Brake system checked and serviced, brake pads/linings in a serviceable condition??	Y N N NA
Service brake a split system?	Y N N NA
Adequate provision made for adjustment of service and park brake systems?	Y N N NA
(1) Combined reservoir for split system?	Y N N NA
(2) If yes, is there a divider fitted?	Y 🔲 N 🔲 NA 🔲
Labelling satisfactory and located on or near brake fluid reservoir cap?	Y N N NA
Service brake failure indicator lamp fitted and functioning correctly?	Y N N NA
Labelling satisfactory with at least the word 'BRAKE,' or ISO symbol ?	Y N N NA
Park brake mechanical only?	Y N N NA N
Park brake indicator a separate Lamp (S), or a combination unit (C) with service brake failure lamp? (Circle S or C).	
Labelling satisfactory with the word 'PARK BRAKE,' or ISO symbol , or if combined with service brake?	Y
Compliance with rule	Y N N NA D
ADR 34/00 - CHILD RESTRAINT ANCHORAGES & CHILD RESTRAINT	1
(Effective date for MA vehicles July 1988) FEATURE	COMPLIANCE
Child Restraint Anchorages provided for each applicable rear seating position?	Y D N D NA D
Anchorages fitted meet Australian equivalent standards by inspection, comparison or test (circle)?	Y O N O NA O
Child Restraint Anchor Fitting installed in at least the centre rear position, unless centre lap sash belt fitted? (Not required when certified to ADR 5/02) If not fitted in centre position note where fitted. 3rd Row L	Y
For positions where 'Anchor Fitting' is not provided, anchorage has 5/16 UNC thread? (Where an M8 thread used for CRA, hook type attaching clip to be fitted).	Y N N NA
Clearance provided around each 'Fitting' to allow latching and unlatching of 'Attaching Clip'	Y N N NA
Location information and instructions for use provided?	Y N N NA N
'Child Restraint Anchorages' more than 230mm rearward of the transverse 'Seating Reference Plane'? (140mm when certified to ADR 5/02)	Y N N NA N
'Child Restraint Anchorage/Fitting' lies within 40 mm of the 'Seating Reference Plane'?	Y N N NA N
Compliance with rule	Y N NA NA NA NA NA NA N
VIN Certificate N° Signature	
VIN Certificate N° Signature	
Notes:	
Version 2.0. 4 January 2044	Danis 40 : (45

ADR 35/00- COMMERCIAL VEHICLE BRAKE SYSTEMS (MB & MC CATEGORY ONLY)

(Effective date July 1988)

Γ ,	-		COMPLIANCE
FEATURE			COMPLIANCE
Service brake system serviced, disc pads/linings in serv	iceable condition on all wheels?		Y O N O NA O
Secondary brake system provided?			Y D N D NA D
If service brake is hydraulic, is it a split system?			Y D N D NA D
(1)Combined reservoir for split system?			Y 🗆 N 🗆 NA 🗖
(2) If yes, is there a divider fitted?			Y 🔲 N 🔲 NA 🔲
Label on or near brake fluid reservoir cap?			Y \square N \square NA \square
Service brake failure indicator:			
(1) Provided?			Y 🔲 N 🔲 NA 🔲
(2) Lamp activation satisfactory?			Y 🔲 N 🔲 NA 🔲
(3) Labelling satisfactory with at least the word 'BRAKI	E', or ISO symbol		y 🗆 n 🗆 na 🗖
Audible indicator provided with single brake power unit?			Y N N NA
For system with brake power units, is a separate gauge	provided for each reservoir?		Y N N NA
Park Brake.			
(1) Retention in applied position mechanical?			y 🗖 n 🗖 na 🗖
(2) Control separate from service brake?			Y 🔲 N 🔲 NA 🔲
(3) Min of 2 separate and distinct movements to release	e?		Y 🗆 N 🗆 NA 🗖
IF NA is it designed to minimise the	ne possibility of inadvertent rele	ase?	y 🗆 n 🗆 na 🗖
(1)Park brake indicator a separate lamp (S), or a combin (indicate S or C)	ned unit (C) with service brake f	ailure lamp?	Y N N NA
(2) Labelling satisfactory with the word 'PARK BRAKE',	'PARKING BRAKE', or 🔘 o	r 🔘 ?	Y N NA NA
		liance with rule	Y \square N \square NA \square
ADR 36/00 - EXHAUST EMISSION CONTROL FOR H	HEAVY DUTY VEHICLES (MB	& MC CATEGOR	RY ONLY, OVER 2.7t GVM)
(E	ffective date July 1988)		
FEATURE			COMPLIANCE
Access to idle air/fuel mixture screw?			Y D N D NA D
Engine emission IM240 test conducted (test report attac	hed)? (delayed)		Y N NA NA NA NA NA
	Comp	liance with rule	Y N N NA
VIN Certifica	ate N°	Signature	
Notes:			

ADR 37/00 - EMISSION CONTROL FOR LIGHT VEHICLES (MA, MB1 & MC1 CATEGORY ONLY UNDER 2.7t GVM) (Effective date for MA vehicles July 1988) **FEATURE COMPLIANCE** Y \square N \square NA \square Readily visible unleaded fuel label affixed near petrol filler inlet(s) or filler cap(s) marked? Filler neck internal diameter more than 21.30 mm and less than 23.6 mm (for unleaded petrol nozzle Y \square N \square NA \square only)? Y \square N \square NA \square Satisfactory label fitted in engine compartment? Y \square N \square NA \square Catalytic converter fitted? Y \square N \square NA \square Engine emission IM240 test conducted (test report attached)? (delayed) $Y \square N \square NA \square$ Compliance with rule ADR 41/00 - MANDATORY OPERATION ON UNLEADED PETROL (MB2 & MC2 CATEGORY ONLY, OVER 2.7t GVM) (Effective date July 1988) COMPLIANCE **FEATURE** Satisfactory unleaded fuel label affixed near petrol filler inlet(s)? Y \square N \square NA \square Filler neck internal diameter more than 21.30 mm and less than 23.6 mm (for unleaded petrol nozzle Y \square N \square NA \square only)? $Y \square N \square NA \square$ Compliance with rule **ADR 42/04 - GENERAL SAFETY REQUIREMENTS** (Effective date for MA vehicles July 1988) This rule covers safety requirements for design and construction to ensure safe operation. **COMPLIANCE FEATURE BONNET LATCHING** $Y \square N \square NA \square$ If bonnet front opening, is a second latching position provided? **CIGAR OR CIGARETTE LIGHTER** Y \square N \square NA \square Activation possible only with switch in "accessory" or "engine on" position? **DIESEL ENGINES** Y O N O NA O Device fitted to prevent inadvertent starting of engine? STEERING SYSTEM Y \Boxed N \Boxed NA \Boxed Steering wheel located centrally or to the right? Y \square N \square NA \square Steering wheel on left and vehicle is for personal use as per VSR Rule 21? **AUTOMATIC TRANSMISSION** Y \square N \square NA \square Fitted with automatic transmission? If YES: Y \square N \square NA \square Starter inoperative in forward or reverse? **EXHAUST OUTLETS** Exhaust pipe extends at least 40 mm beyond rearmost unsealed joint of floor-pan? Y \square N \square NA \square Exhaust outlet within vehicle perimeter in plan? Y \square N \square NA \square If exhaust discharges to the side of vehicle is it to the right side and downwards between 15 deg and 45 deg to the horizontal? Y \square N \square NA \square If the exhaust discharges to the rear of the vehicle, is it between 10 deg above and 45 deg below Y \square N \square NA \square horizontal? VIN Certificate N° Signature

VIN		Certificate N°	Signature	
(3) Is the device	s for operating the wipers	s and washers within easy reach	or the driver?	Y LI N LI NA LI
	0 0	h directs water onto the swept a		Y D N D NA D
-	iven windscreen wiping s	-	Cu. IO	Y D N D NA D
	IPERS AND WASHERS			
		sture from the windscreen?		YUNUNAU
DEMISTING OF V				Y O N O NA O
WARNING DEVICE Itted with at leas		implitude and frequency charact	eristics?	Y N N NA N
		- Provided Will Momentary type s	monos or varvos.	Y N NA NA NA NA NA
he opening of the		provided with momentary type s	witches or valves?	
F NA, is there de:	ign features to enable the	ows in close proximity of the drive driver to turn off the rear windo		Y D N D NA D
······································			0	y 🗆 n 🗆 na 🗆
If power w incorporat		te with the key removed is an au	tomatic reverse function	Y N N NA NA NA
	r's door is operated withi a further 45 seconds	n the 45 second period, windows	remain operational for not	Y N N NA
	3	vindows remain operational for n		Y D N D NA D
key? Except				Y
	vindows available only thi	rough use of		
s alternative vent	lation adequate?			Y O N O NA O
Can at least half o f NA:	f the windows be opened	?		Y N N NA
WINDOWS AND	_			
Oriver's visibility o	f images other than for dr	iver's aid prevented?		Y N N NA N
Obstruction of driv	er's vision and impedime	nt to driver or passenger movem	ent prevented?	Y 🔲 N 🔲 NA 🔲
f YES:	i visual display monitor ii	ilicu:		Y N N NA
	r visual display monitor fi			
designed for off-ro	iad operation? D VISUAL DISPLAY UNI	TS.		
han 230 mm abo	e the ground for vehicles	ents of clause 15.2.2: do mud-fla s other than off-road vehicles, an		Y N N NA
For MB and MC (
, ,	s cover at least as shown	in Fig. 1 or 2 of ADR 42/00 as a 1C)?	oplicable? (Fig. 1 for	Y N N NA
	direct contact in collision			Y N N NA N
(1) Direct d	ownwards stones, mud, id	ce and snow as far as practicable	?	Y N N NA
	eels shrouded by wheel g	juards that will:		
	(MUDGUARDS)	ons in none of the vehicle unous	ii ucteu ?	
FIELD OF VIEW	ther eide and in all direct	ions in front of the vehicle unobs	tructod?	Y N N NA

TYRE AND RIM SELECTION	
Is a tyre placard fitted?	Y O N O NA O
Does the placard contains the following information:	I D N D NA D
(1) Manufacturers recommended tyre size?	Y O N O NA O
(2) Recommended cold inflation pressures in Kpa?	Y D N D NA D
(3) Recommended load rating and speed category?	Y O N O NA O
Maximum load rating and speed category of tyre fitted equal to or greater than that on the place	
Are all tyres on the placard included on the RVD?	Y N N NA D
Are all tyres on the placara included on the RVD:	
Part number if shown on the placard?Pt No	#
Compliance	with rule Y N N NA N
ADR 43/01 - VEHICLE CONFIGURATION & MARKING	G
(Effective date for MA vehicles July 1988)	
FEATURE STUMBER	COMPLIANCE
Engine number stamped, legible and satisfactorily legated?	Y D N D NA D
Engine number stamped, legible and satisfactorily located?	
Engine number be readily seen when engine installed in vehicle?	Y D N D NA D
REGISTRATION PLATES All parts of front and room number plate (made on par Fig. 1 of ADD/1/00) helpey 1200 mm front	
All parts of front and rear number plate (made as per Fig. 1 of ADR43/00) below 1300 mm fron ground?	YUNUNAU
No part of front and rear number plate obscured by any part of or equipment on the vehicle?	Y 🗆 N 🗆 NA 🗆
PROJECTION OF EQUIPMENT	y \square N \square NA \square
All front and rear projections of equipment less than 1200 mm?	
Compliance	with rule Y N N NA
ADR 44/02 - SPECIFIC PURPOSE VEHICLE REQUIREME	ENTS
(Effective date for MA vehicles July 1988)	COMPLIANCE
L.P.G. FUELLED VEHICLES	COMPLIANCE
Vehicle clearly permanently marked in a conspicuous position within the engine compartment following information?	with the Y N N NA
(1) Installed as per AS1425-1989?	Y O N O NA O
(2) Identification of the installer? (If not the same as the manufacture, note details).	Y O N O NA O
(3) Date of installation?	Y O N O NA O
Are labels to be affixed to registration plates and supplied for inspection, at least 25 mm squares.	
red in colour?	re and Y N N NA N
BONNET LATCHING	y \square N \square NA \square
If bonnet front opening, is a second latching position provided?	
CIGAR OR CIGARETTE LIGHTER Activation possible only with switch in "accessory" or "engine on" position?	Y N N NA
reavalion possible only with switch in accessory of engine on position:	I
VIN Certificate N° Sign	ature
, samuala i	
Notes:	

ADR 60/00 - CENTRE HIGH MOUNTED STOP LAMPS (Effective date for MA vehicles July 1988)	
FEATURE	COMPLIANCE
Central High mounted Stop Lamp fitted?	Y N N NA D
Lamp design provides for easy replacement of the globe without the use of special tools?	Y N N NA
Mounted on the vehicles median longitudinal plane?	Y N N NA
Mounted with no part of the lens lower than the bottom edge of the rear window by more than 152 mm for convertibles, and 77 mm for other vehicles?	Y N N NA
Compliance with rule	Y N N NA
VEHICLE DIMENSIONS	
FEATURE	COMPLIANCE
Vehicle meets relevant requirements of AVSRs?	Y N N NA
NOTE: If the answer N (No) appears in any "Compliance with rule" box, the compliance Approval Code LO1	cannot be certified under
VIN Certificate N° Signature	
VIN Certificate N° Signature	