

Compliant Products Register for Tactile Ground Surface Indicators (TGSI)

Assessed as compliant to AS/NZS 1428.4.1:2009 and other criteria as determined by Transport and Main Roads.

TGSI are truncated cones and or bars installed on the ground or floor surface designed to provide pedestrians who are blind or vision impaired with warning or directional orientation information.

March 2024



Copyright

© The State of Queensland (Department of Transport and Main Roads) 2024.

Licence



This work is licensed by the State of Queensland (Department of Transport and Main Roads) under a Creative Commons Attribution (CC BY) 4.0 International licence.

CC BY licence summary statement

In essence, you are free to copy, communicate and adapt this work, as long as you attribute the work to the State of Queensland (Department of Transport and Main Roads). To view a copy of this licence, visit: https://creativecommons.org/licenses/by/4.0/

Translating and interpreting assistance



The Queensland Government is committed to providing accessible services to Queenslanders from all cultural and linguistic backgrounds. If you have difficulty understanding this publication and need a translator, please call the Translating and Interpreting Service (TIS National) on 13 14 50 and ask them to telephone the Queensland Department of Transport and Main Roads on 13 74 68.

Disclaimer

While every care has been taken in preparing this publication, the State of Queensland accepts no responsibility for decisions or actions taken as a result of any data, information, statement or advice, expressed or implied, contained within. To the best of our knowledge, the content was correct at the time of publishing.

Feedback

Please send your feedback regarding this document to: tmr.techdocs@tmr.qld.gov.au

Contents

1	Introduction	1
1.1	Relevant information for installation	1
2	Definitions	1
3	Disclaimer	1
4	Standards	2
4.1	Governing manuals, specifications or guidelines	2
5	'Compliant' Tactile Ground Surface Indicators	3
6	Contact for enquiries and proposed changes	15
Арр	endix A – Compliant products criteria checklist	16

1 Introduction

This is a controlled document that presents a listing of Tactile Ground Surface Indicator (TGSI) products, which the Department of Transport and Main Roads considers to be compliant with:

- a) Australian Standard AS/NZS 1428.4.1: Design for access and mobility, Part 4.1: Means to assist the orientation of people with vision impairment Tactile ground surface indicators
- b) Australian Standard AS 4586 Slip resistance classification of new pedestrian surface materials, and
- c) other criteria as specified by the department.

Transport and Main Roads does not recommend any specific TGSI for particular applications. Practitioners will need to assess the style most suitable for the particular application, taking into account substrate, luminance contrast, aesthetics, availability, consistency in areas and whole-of-life cost.

Companies that supply TGSI may distribute or supply and install a range of products. Compliant TGSI listed in Table 5 are the products that have satisfied the criteria specified by the department.

This document is subject to periodic review and will be updated when new product registrations are received. If printed, practitioners are requested to access the <u>Transport and Main Roads website</u> for confirmation of the latest products register.

1.1 Relevant information for installation

Where TGSI are installed on a ramp steeper than 1 in 14 (such as the face of a kerb ramp that has a slope of 1 in 8), a wet pendulum test result of P5 is required for the product. Please refer to Standards Australia Handbook SA HB 198 Guide to the specification and testing of slip resistance of pedestrian surfaces Table 3B: Wet pendulum test or oil-wet inclining platform classifications for applications where the National Construction Code does not require slip resistance.

2 Definitions

 Refer AS/NZS 1428.4.1 Design for access and mobility, Part 4.1: Means to assist the orientation of people with vision impairment – Tactile ground surface indicators.

3 Disclaimer

The materials presented in this publication are distributed by the Department of Transport and Main Roads for and on behalf of the State of Queensland as an information source only. Transport and Main Roads makes no statements, representations or warranties about the accuracy or completeness of, or application of, and you should not rely on, any information contained in this publication. Transport and Main Roads disclaims all responsibility and all liability (including without limitation, liability in negligence) for all expenses, losses, damages and costs which you might incur as a result of the information contained in this publication being inaccurate or incomplete in any way, or for any other reason whatsoever.

In no event will the State of Queensland be liable for any damages including loss of profits, lost savings, liability in negligence or other indirect, incidental, special or consequential damages arising out of the use or publication of any information contained in this publication.

4 Standards

4.1 Governing manuals, specifications or guidelines

- AS/NZS 1428.4.1 Design for access and mobility, Part 4.1: Means to assist the orientation of people with vision impairment – Tactile ground surface indicators
- AS 4586 Slip resistance classification of new pedestrian surface materials
- Standards Australia Handbook SA HB 198 Guide to the specification and testing of slip resistance of pedestrian surfaces
- Queensland <u>Manual of Uniform Traffic Control Devices</u>
- Road Planning and Design Manual 2nd edition
- Transport and Main Roads <u>Standard Drawings</u> 1446,1447, KRG1 and KRG2.
- Transport and Main Roads Specification (Measurement) MRS14 Road Furniture, and
- Transport and Main Roads <u>Technical Specification</u> MRTS14 *Road Furniture*.

5 'Compliant' Tactile Ground Surface Indicators

Table 5 – 'Compliant' Tactile Ground Surface Indicators

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Sirus TGSI™ large format integrated warning plate #14-1		METAL P5, R11 platinum (displayed), Allgrip, natural or anodised metal sizes available 2400, 1500, 1200, 900 in 600 or 300 mm wide	Alltac Pty Ltd www.alltac.com.au Phone: 1300 255 822 / 1300 ALL TAC Email: info@alltac.com.au Installation warranty 10+ years for foot traffic ability to touch up insitu extend life UV resistance warranty minimum 10 years
Sirus TGSI™ large format integrated directional plate #14-2		P5, R11 Allgrip sizes available 1500, 1200, 900, 600, 300 in 600 or 300 mm wide	Other information Australian-made products, large format metal plates (custom angles, sizes, colours, and widths available), low profile 1.6 mm base thickness, one-piece with patented self-cleaning hazard dome registered design and trademark protected products Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but
Allstar Warning Discrete #14-3		P5, R12 • stainless steel metal studs	may be suitable for temporary exterior use.

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
CME Integrated Warning #16-1		FIBRE POLYMER fibreglass reinforced resin polymer P5, R11 white and yellow 300 mm x 600 mm amm thick plate cone height 5mm	CME Composite Materials Engineering Pty Ltd www.cmetactile.com.au Bruno Tassone Mobile: +61 473 555 717 Email: Bruno.Tassone@composite.com.au Phone: 03 8720 7600 Manufacturer warranty 10 years material manufacturer warranty (conditional warranty)
CME Integrated Directional #16-2		P5, R12 Note: Deteriorated polymer may affect waterways and associated environment.	UV resistance warranty tested to Australian UV and weather conditions up to 10 years (conditional warranty) Installation warranty usually provided by the separate installer Luminance reflectance value (LRV) tested. white and yellow Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Austact® - Warning Stud #7-1		POLYMER (polyurethane) P5, R11 installation warranty 2 years individually inserted indicators (discrete) suited to new or retrofit installations adhesive-free installation UV resistant polymer 9 colours available Note: Deteriorated polymer may affect waterways and associated environment.	CTA (QLD) Pty Ltd www.ctagroup.com.au Phone: 1300 282 282 Email: craig.rogers@ctagroup.com.au UV resistance warranty • may be affected by high UV exposure Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.
Austact® – Directional Strip #7-2		P5, R11	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Rhinotac® Warning Plate #7-3		FIBRE REINFORCED POLYMER P5, R12 installation warranty 2 years installed with fixings and adhesive retrofit solution internal & external	CTA (QLD) Pty Ltd (continued) www.ctagroup.com.au Phone: 1300 282 282 Email: craig.rogers@ctagroup.com.au . UV resistance warranty • may be affected by high
Rhinotac® Directional Plate #7-4		P5, R13 • installation warranty 2 years Note: Deteriorated polymer may affect waterways and associated environment.	
PolyPad® Warning Pad (directional product is a variant, not registered) #7-5		RUBBER P5, R11 Installation warranty 2 years Internal & external 9 colours available	
PolyStud® Warning Studs #7-6		POLYMER P5, R11 Installation warranty 5 years discrete adhesive-free installation 7 colours available	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Eigen FibreTac Warning #11-1		FIBRE POLYMER fibreglass reinforced resin polymer P5, R12 • new or retrofit installation Note: Deteriorated polymer may affect waterways and associated environment.	EIGEN HOLDINGS PTY LTD (Eigen Tactile) www.eigentactile.com Phone: 03 9018 7954 Michael Lim Mobile: 0412 544 795 Email: info@eigentactile.com Manufacturer warranty • 5 years material manufacturer warranty Installation warranty • usually 24 months provided by the separate installer Warranty conditions
Eigen FibreTac Directional #11-2		P5, R11	warranty may void if installation do not follow minimum 10 days 'bleed' requirement for asphalt surface, and/or minimum 7 days 'dried' requirement for concrete surface Other information UV stabilised resin reinforced with embedded fibreglass, may be affected by high UV exposure Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
ESP Warning Integrated Surface Applied Access Tile #4-1		FIBRE POLYMER fibre reinforced polymer P5, R11 • screwed and glue application, perfect for retrofit installation	ESP Australia Pty Ltd www.espaust.net.au Mathew Shallard Phone: 1300 665 761 E: sales@espaust.net.au Manufacture warranty 10 years manufacturer's warranty (conditional warranty) Installation warranty
ESP Warning Integrated Cast-In-Place Access Tile #4-2		P5, R11 • pressed into place for new concrete pours	Usually provided by installation contractor <u>UV resistance warranty</u> Not available (although Supplier asserts that product includes UV stabilizer designed for QLD conditions). Product may be
ESP Directional Surface Applied Access Tile #4-3•		P4, R11 Due to the P4 rating, this product suits flat surfaces but not ramps. Note: Deteriorated polymer may affect waterways and associated environment.	affected by high UV exposure. Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.
ESP Directional Cast-In-Place Access Tile #4-4		P4, R11 Due to the P4 rating, this product suits flat surfaces but not ramps.	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Warning Tactile #10-1		POLYMER polyurethane, PU P5, R11 300 mm x 300 mm black, warning yellow, terracotta, medium grey	Guardian Tactile Systems Pty Ltd www.guardiantactile.com 08 9240 1888 sales@guardiantactile.com Polyurethane products 10 year warranty (manufacturing, UV resistance, excludes installation) Fibre reinforced resin polymer (FRP)
FRP Warning Tactile #10-3		fibre reinforced resin polymer – FRP P5, R12 • 300 mm x 600 mm • black, yellow, white Note: Deteriorated polymer may affect waterways and associated environment.	products 2 year warranty (manufacturing, UV resistance, excludes installation). Product may be affected by high UV exposure Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.
FRP Directional Tactile #10-4		P5, R11	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Renzo Classic – Warning (Discrete) #18-1		POLYMER P5, R11 Note: Deteriorated polymer may affect waterways and associated environment.	Korb Pty Ltd https://www.korb.com.au/ Contact: Julien Buhagiar info@korb.com.au 1300 00 KORB (5672) Product warranty: 5 years (check limitations). Product may be affected by high UV exposure. Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.
Renzo Tile – Warning (Integrated) #18-2		POLYMER P5, R11 Note: Deteriorated polymer may affect waterways and associated environment.	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Ultimate Tactile Integrated Hazard #13-1		POLYMER recycled polyethylene terephthalate (RPET) P5, R11 • made from recycled material, plastic bottles • tactile suited to new or retrofit installations • 300 mm x 600 mm • black, yellow or white Note: Deteriorated polymer may affect waterways and associated environment.	SAFETY XPRESS Pty Ltd www.safetyxpress.com.au Phone: 1300 049 246 (VIC) Email: gldsales@safetyxpress.com.au Nic Eason (QLD) Mobile: 0435 760 692 Life of warranty • high pedestrian foot traffic 5+ years material manufacturing warranty only, excludes installation warranty Installation warranty • installation warranty is supplied by third party which will follow the installation guideline Guaranteed 5 years of UV protection and colour fasting • an ultra UV stabilised resin guaranteed to last without fading for at least 5 years, and luminance contrast tested • Australian made Note: Products with less than ten year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
316 Marine Grade TGSI Warning Discrete Studs #15-1		METAL Stainless steel P5, R11	supplym8 QLD PTY LTD www.supplym8qld.com.au Email: info@supplym8qld.com.au QLD representatives Rob Ninness, Suzy Black Phone: 0487 132 575 Warranty guarantee installation 10 years with terms and conditions
FRP Hazard Integrated Tactile #15-2		FIBRE POLYMER fibreglass and resin polymer P5, R12 2 mm & 20 mm thick 600 mm x 300 mm	Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.
FRP Directional Integrated Tactile #15-3		P5, R13 2 mm & 20 mm thick 600 mm x 300 mm	
Pre-cast Concrete Tactile Pavers, Warning #15-4		PRECAST REINFORCED CONCRETE PAVER P5, R11 300 mm x 300 mm	
Pre-cast Concrete Tactile Pavers, Directional #15-5		P5, R11	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
TSA Warning Discrete TGSI Single Stem #12-1		POLYMER polyurethane plastic P5, R12 • tactile suited to new or retrofit installations	Tactile Systems Australia (TSA) www.tactilesystems.com.au Contact: Sam Tatters Phone: 07 5580 6993 Email: sales@tactilesystems.com.au Manufacturing and UV resistance warranty
TSA Warning Discrete TGSI Bladed Shaft #12-2		Polyurethane plastic P5, R12 Installation warranty • 2 year Note: Deteriorated polymer may affect waterways and associated environment.	manufacturing and UV resistance warranty is not available. UV performance has been tested. Product may be affected by high UV exposure. Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.
TSA Warning Integrated TGSI Future-Tech #12-3		FIBRE-POLYMER fibreglass reinforced polymer P5, R12 • tactile suited to new or retrofit installations	
TSA Directional Integrated TGSI Future-Tec4 #12-4		600 mm x 300 mm 3 mm thick black, yellow, white, terracotta Product warranty 5 years – may be affected by high UV exposure	

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
TSA Directional Integrated TGSI Paver #12-5		Wet cast concrete P5, R12 • 300 mm x 300 mm • 40 mm & 60 mm thick • black, yellow, ivory, grey, red Product warranty • 5 years	
TSA Warning Integrated TGSI Paver #12-6			

Name / TGSI type / dept. internal ref	Product picture	Product description (material, rating, size)	Supplier website / contact / warranty conditions
Flexi Pave Integrated Warning #1-1		FIBRE POLYMER CONCRETE fibre reinforced polymer concrete P5, R13 • yellow, black, ivory • size: 300 mm x 600 mm • thickness: 2mm	United Civil Constructions Pty Ltd (UCC) www.ucctactile.com.au Phone: (03) 9701 8498 Mobile (Danny Chee): 0417 322 886 E-mail: unitedcivil@hotmail.com • suited to new or retrofit installations. Installation warranty • 7 years, warranty is available first 12 months with no conditions; after year 1, warranty is conditional on 2-yearly maintenance UV resistance warranty • UV resistance warranty is available first 12 months • UV resistant paint can be renewed
Flexi Pave Integrated Directional #1-2		P5, R13 yellow, black, ivory size: 300 mm x 600 mm thickness: 2 mm Note: Deteriorated polymer may affect waterways and associated environment.	every 2 years to increase the usage life and restore UV resistant capability • UV protection is approximately 95% when sealed with the paint, namely Dulux road master line marking A1 • Product may be affected by high UV exposure Manufacturing warranty • warranty is available first 12 months with no condition Other information • Australian made products Note: Products with less than 10 year warranty for manufacture or installation may not suit long term exterior use but may be suitable for temporary exterior use.

6 Contact for enquiries and proposed changes

To be included in the 'Compliant Products Register', TGSI suppliers should supply evidence to the contact following, demonstrating that the product meets the criteria requirements specified in Appendix A *Compliant products criteria requirements*. Upon satisfying the criteria, the supplier will be included on this 'Register'. If you have any other questions regarding this document or if you have feedback on the performance of certain products, please contact:

Contact Vulnerable Road User Team, Traffic Engineering Unit, Engineering &

Technology "Branch

Email CyclePedTech@tmr.qld.gov.au

Appendix A – Compliant products criteria checklist

Products are required to meet the following criteria to be included on the 'Compliant Products Register' of tactile ground surface indicators (TGSI).

M – Mandatory Requirements (if applicable); D – Desired Requirements; I – Information only If you do not think a specific criterion is applicable to your product, please supply reasons.

1. M Slip resistance, tested in accordance with AS 4586 *Slip resistance classification of new pedestrian surface materials* linked to the specific product being registered. Tests results confirming the product is in accordance with both slip resistance tests is required. If the manufacturing process has changed, new tests are required.

'Wet Pendulum Test' assessment group = P4 or P5

'Oil Wet Inclining Platform Test' assessment group = R11 or better

- **2. M** TGSI design (size and spacing) compliant with AS/NZS 1428.4.1 Design for access and mobility, Part 4.1: Means to assist the orientation of people with vision impairment Tactile ground surface indicator
- **3. M** Minimum guarantee of product including UV resistance and installation (if applicable) of 5 years
- **4. M** For ceramic TGSI tile products, minimum breaking strength = 1100N tested in accordance with AS ISO 10545.4 *Ceramic tiles, Method 4: Determination of modulus of rupture and breaking strength*
- **5. M** For ceramic TGSI tile products, water absorption (E) <= 3%, tested in accordance with AS ISO 10545.3 Ceramic tiles, Method 3: Determination of water absorption, apparent porosity, apparent relative density and bulk density.
- 6. D Installation and production specification.
- **7. D** Variability in products to provide luminance contrast specified in AS 1428.4.1 to be achieved in typical footways and kerb ramps (concrete, asphalt, pavers).
- 8. M Product name and TGSI type (Discrete or Integrated & Directional or Warning
- **9. M** Material type. Major material component and generic classification only (Ceramic, Concrete, Plastic, Polymer, Fibre Polymer or Metal)