

Main Roads Technical Standard

MRTS232

Provision of Field Processors

October 10

 **Queensland** Government

TRADEMARKS ACKNOWLEDGEMENT

Terms mentioned in this document that are known or understood to be trademarks, whether registered or not, have been identified. Where trademarks have been confirmed as registered in Australia, this has been indicated by the addition of the ® symbol, otherwise the ™ symbol is used. While all care has been taken to identify trademarks, users should rely on their own inquiries to determine trademark ownership. Use of a term in this document as a trademark should not be regarded as affecting the validity of any trademark.

IMPORTANT INFORMATION

The requirements of this document represent Technical Policy of the department and contain Technical Standards. Compliance with the department's Technical Standards is mandatory for all applications for the design, construction, maintenance and operation of road transport infrastructure in Queensland by or on behalf of the State of Queensland.

This document will be reviewed from time to time as the need arises and in response to improvement suggestions by users. Please send your comments and suggestions to the feedback email given below.

FEEDBACK

Your feedback is welcomed. Please send to mr.techdocs@tmr.qld.gov.au.

DISCLAIMER

This publication has been created for use in the design, construction, maintenance and operation of road transport infrastructure in Queensland by or on behalf of the State of Queensland.

Where the publication is used in other than the department's infrastructure projects, the State of Queensland and the department gives no warranties as to the completeness, accuracy or adequacy of the publication or any parts of it and accepts no responsibility or liability upon any basis whatever for anything contained in or omitted from the publication or for the consequences of the use or misuse of the publication or any parts of it.

If the publication or any part of it forms part of a written contract between the State of Queensland and a contractor, this disclaimer applies subject to the express terms of that contract.

COPYRIGHT

Copyright protects this publication. Except for the purposes permitted by and subject to the conditions prescribed under the Copyright Act, reproduction by any means (including electronic, mechanical, photocopying, microcopying or otherwise) is prohibited without the prior written permission of the department. Enquiries regarding such permission should be directed to the Pavements, Materials, Geotechnical and Standards Division, Queensland Department of Transport and Main Roads.

© State of Queensland (Department of Transport and Main Roads) 2010



<http://creativecommons.org/licences/by-nc-nd/2.5/au>

Table of Contents

	Page
1 INTRODUCTION	1
1.1 Purpose	1
1.2 Scope	1
2 REFERENCE DOCUMENTS	1
3 DEFINITION OF TERMS	1
4 QUALITY SYSTEM REQUIREMENTS	2
5 FUNCTIONAL REQUIREMENTS	2
5.1 General	2
5.2 STREAMS Compatibly	2
6 EQUIPMENT COMPONENTS	2
6.1 Field Processor	2
6.2 Field Processor Configuration	2
6.3 STREAMS Compliance Testing	3
7 TECHNICAL SPECIFICATIONS	3
7.1 General	3
7.2 CPU and Motherboard	3
7.3 System Resources	3
7.4 I/O Requirements	4
7.5 Expansion Bus Interface/s	5
7.6 Field Processor Enclosure	5
8 POWER SUPPLY UNIT	6
8.1 General	6
9 STANDARDS COMPLIANCE	6
10 SERVICE, WARRANTY, GUARANTEE AND REPAIR	6
11 PACKAGING AND DELIVERY	6
12 MECHANICAL AND PHYSICAL REQUIREMENTS	6
12.1 Environmental Conditions	6
13 INSTALLATION REQUIREMENTS	7
14 ELECTRICAL	7
15 TESTING AND COMMISSIONING	7
16 DOCUMENTATION	7
17 TRAINING	7
18 MAINTENANCE	7
19 HANDOVER	7

Provision of Field Processors

1 INTRODUCTION

1.1 Purpose

This standard defines the design, supply, installation, testing and commissioning, performance, documentation, training and maintenance requirements for the provision of a STREAMS compatible Field Processors (FP).

A Field Processor is an industrial, microprocessor-based computer suitable for use in traffic management applications hosted by the STREAMS System. They are used by the STREAMS system to provide a platform to host the distributed components of the STREAMS software that interface to the field equipment.

Field Processors are used in a number of different applications by STREAMS. The units may be mounted in cabinets on roadside plinths or within traffic signal controller cabinets. In some situations, they may be deployed within Traffic Management Centres to interface to ITS infrastructure and networks.

1.2 Scope

The Field Processor is a component of the STREAMS system which forms the basis of the Main Roads ITS Platform and Transport Management System.

2 REFERENCE DOCUMENTS

The requirements of the referenced documents listed in Table 3 of MRTS201 and Table 2 below apply to standard. Where there are inconsistencies between this standard and referenced MRTS, the requirements specified in this standard shall take precedence.

Table 2 – Referenced Documents

Document ID	Document Name / Description
MRTS232.1	Annexure - Provision of Field Processors Specific Contract Requirement
MRTS201	General Equipment Requirements
MRTS245	Principal's Telecommunications Network
AS 60529	Degrees of protection provided by enclosures (IP Code)
AS/NZS 4251.1	Electromagnetic Compatibility (EMC) – generic Emission Standard

3 DEFINITION OF TERMS

The terms defined in MRTS201 apply to this standard. Additional terminology relevant under this standard are defined in Table 3 below.

Table 3 – Definitions

Term	Definition
ACMA	Australian Communications and Media Authority
BIOS	Basic Input Output System
CPU	Central Processing Unit
C Tick	An identification trademark registered to the government authority (ACMA) which indicates compliance with EMI (electromagnetic interference) standards. C-Tick covers only emission standards both conducted and radiated.
DIMM	Dual Inline Memory Module

Term	Definition
EIA	Electronics Industries Association
Field Processor	Ruggedized field computer used to connect field devices to the ITS Network
FP	Field Processor
GB	Gigabyte
ITS	Intelligent Transport Systems
ITS Network	Principal's Telecommunications Network in accordance with MRTS245
MB	Megabyte
PC	Personal Computer
PC/104	PC/104-Plus An embedded computer standard controlled by the PC/104 Consortium
PnP	Plug and Play
RAM	Random Access Memory
Site Identifier	A non-volatile memory device that stores a site identification. It connects to a dedicated serial port on the field processor.
SO DIMM	Small Outline - Dual Inline Memory Module
STREAMS	Main Roads ITS Platform and Transport Management System
UART	Universal Asynchronous Receiver Transmitter
USB	Universal Serial Bus

4 QUALITY SYSTEM REQUIREMENTS

The quality system requirements defined in MRTS201 apply under this standard. There are no additional quality system requirements for equipment provided under this standard.

5 FUNCTIONAL REQUIREMENTS

5.1 General

The FP shall be an industrial PC and shall interface to, control and manage the operation of field systems and devices that form part of ITS applications. The scope of such functionality for each device and/or system is described in the respective MRTS.

The FP shall be located within a roadside field cabinet or within a Traffic Signal Controller cabinet.

5.2 STREAMS Compatibly

The Field Processor shall be capable of operating in the STREAMS environment.

6 EQUIPMENT COMPONENTS

6.1 Field Processor

The field processor equipment shall consist of:

- a) a FP, including memory and input / output interface cards; and
- b) a separate power supply.

6.2 Field Processor Configuration

The Contractor shall provide field processors which meet the requirements specified in this standard. In addition, the contractor shall engage Transmax Pty Ltd to confirm that the hardware is suitable for installation of the STREAMS software. The STREAMS software to be run on the field processor will be provided by

Transmax Pty Ltd. The Contractor shall engage Transmax Pty Ltd for the loading and configuration of the STREAMS software onto the field processor.

6.3 STREAMS Compliance Testing

Field Processor units supplied under this contract are required to undergo STREAMS Level 1 compliance testing. The Contractor shall provide a STREAMS compatibility certificate to the Administrator for acceptance.

7 TECHNICAL SPECIFICATIONS

The Field Processors shall comply with the following minimum requirements unless described otherwise in the attached Annexure MRTS232.1 - Provision of Field Processors.

7.1 General

The operational requirements defined in MRTS201 shall apply to equipment provided under this standard. Additional operational requirements for equipment are described below.

The FP shall meet the following general requirements:

- a) a 'technology guarantee' backward compatibility of future replacement products for a period of at least five years shall be provided;
- b) no hardware modules shall be configured using "Plug and Play" (PnP). The PnP functionality shall not be provided or shall be disabled (and the module configured) by jumper/BIOS;
- c) all hardware shall be certified as compatible with Linux kernel 2.4.18. Supported chipsets are itemised in Appendix A "Supported Chipsets";
- d) all hardware shall be compliant with AS/NZS 4251.1 (EN 50081.1) for C-Tick approval; and
- e) fanless design.

7.2 CPU and Motherboard

The CPU and motherboard shall meet the following requirements:

- a) the processor shall be of a 32-bit architecture, compatible with and providing the performance of at least an Intel Celeron 400 MHz or as defined in the attached annexure;
- b) the processor board architecture shall be functionally compatible with the IBM PC/AT specification; and
- c) the processor board shall be capable of stand-alone operation without keyboard, video, disk drive, etc. connected.
- d) the processor card shall be able to operate from an input voltage in the minimum range of +5 V to +24 V DC.
- e) the field processor power connector shall be fastened and keyed to ensure that the positive and negative inputs cannot be reversed.

7.3 System Resources

The FP system resource requirements include:

- a) the system shall be supplied with minimum 128MB RAM, expandable to minimum 512MB, in standard DIMM or SO-DIMM format or as defined in the attached annexure;
- b) the system shall be supplied with minimum 128MB solid state removable industrial grade compact flash disk and be capable of supporting up to a 2Gbyte removable compact flash disk or as defined in the attached annexure. The compact flash disk shall be bootable and have direct BIOS support;
- c) the system shall provide a battery-backed (or equivalent) "Real Time Clock", capable of retaining accurate date/time for a minimum of 12 months without mains power. The clock shall be accurate to within 1 second per day; and

- d) the system shall provide a dedicated hardware watchdog timer circuit with the ability to reset the system on timeout. It shall be possible to enable and disable the watchdog timer either by software or by jumper/BIOS, and provide a range of timeout values from 1 second to several minutes.

7.4 I/O Requirements

The FP shall provide the following I/O interfaces:

- a) Serial Interfaces:
- i. one (1) EIA/RS 232C serial port for the console terminal;
 - ii. one (1) EIA/RS 232C serial application port;
 - iii. minimum two (2) serial ports that are individually software configurable for either EIA/RS 232C or EIA/RS 422;
 - iv. serial port chipset shall use a 16C550 or compatible UART;
 - v. all serial ports shall be capable of 300 to 115 200 bits per second;
 - vi. base addresses and IRQs selectable by jumper/BIOS;
 - vii. all serial ports are to be available on the front panel by D style 9 way connectors with locking screws;
 - viii. termination resistors for ports in EIA/RS 422 can be jumpered; and
 - ix. isolation shall be provided for ports when configured for the EIA/RS-232 and EIA/RS-422 standards. Isolators shall suppress at least 3KV and be replaceable without opening the enclosure
- b) Parallel Interface:
- i. minimum one x EPP/ECP Parallel port for the Site Identification Dongle, compatible with IBM LPT: standard,
 - ii. base address and IRQs selectable by jumper/BIOS; and
 - iii. connections made by D Style 25 way connectors with locking screws.
- c) Digital Input / Output:
- i. minimum 1 x 8 Bit port. Each bit is capable of being configured as either Input or Output;
 - ii. all Outputs to be capable of driving one standard TTL load;
 - iii. each input capable of generating interrupts on rising/falling/both edges of each input pulse;
 - iv. base addresses and IRQs selectable by jumper/BIOS;
 - v. connections made by an appropriate connector mounted on the enclosure complete with locking screws.
- d) Network Adaptor:
- i. 10/100 or 10/100/1000 megabit Ethernet adaptor with Linux driver. For Linux version refer clause 7.1 General;
 - ii. connection made by standard Ethernet RJ45 modular connector on the enclosure; and
 - iii. base addresses and IRQs selectable by jumper/BIOS;
 - iv. any additional Ethernet ports as defined in the attached annexure.
- e) USB Interface:
- i. minimum two (2) USB 2.0 compliant universal serial bus port.
 - ii. the USB connections on the enclosure shall provide a securing mechanism to overcome vibration issues relating to harsh environments. Preference will be for a connection utilising a thumb screw or similar securing device. The contractor shall provide details on the securing mechanism being proposed for the unit.

- f) Display Adaptor:
 - i. VGA monitor support with minimum 1MB video memory capable of 1024 x 768 resolution at 65536 colours;
 - ii. The display adapter is for diagnostic purposes only. An external VGA connector is not required on the enclosure; and
 - iii. optionally, an additional interface to LVDS LCD display with connection to panel made by standard D-Sub 26-pin connector with securing clips.
- g) Keyboard Interface:
 - i. standard AT 101-key keyboard interface, with connection made by PS/2-style mini-DIN connector.
 - ii. keyboard interface is for diagnostic purposes only. An external keyboard connector is not required on the enclosure.
- h) Mouse Interface:
 - i. standard mouse interface, with connection made by PS/2-style mini-DIN connector.

7.5 Expansion Bus Interface/s

The Expansion Bus interface requirements include:

- a) Where required, the PC/104 bus shall provide both a PC/104 bus conforming to V2.2 or later electrical and mechanical specifications and a PC/104-Plus bus conforming to V2.0 or later electrical and mechanical specifications. All adaptor cards are to provide 'stack-through' bus connection (except the processor card, which may be a non stack-through 'base' card).

7.6 Field Processor Enclosure

Enclosure-related requirements for the FP shall include:

- a) FPs will normally be mounted within telecommunications field cabinets that comply with MRTS201, or traffic signal controller cabinets. A space of approximately 300 x 200 x 200 mm shall be sufficient for mounting the field processor within these cabinets;
- b) LED indicators for the power and disk drive status shall be provided on the external face of the enclosure on the same face as the data connectors;
- c) All interface ports shall be clearly labelled with indelible markings;
- d) The FP enclosure shall be suitable for mounting on a DIN rail bracket conforming to EN50022;
- e) Connectors for all data interfaces and power supply shall be provided with a locking mechanism, either screwed or latching;
- f) Metallic construction of high quality, sealed against dust and moisture to a minimum rating of IP51, as specified in AS 60529;
- g) No moving parts (e.g. no fan forced cooling);
- h) To meet the temperature specifications, the field processor may use the metal enclosure as a heat sink. Suitable measures shall be employed to all external the heat sinks to prevent damage/ injuries from high temperatures to other equipment/ personnel;
- i) The enclosure shall be constructed in a manner that will prevent entry and nesting of vermin; and
- j) The enclosure shall be made of corrosion resistant material or be treated with corrosion resistant coatings to ensure it remains corrosion free under normal road-side conditions for a minimum period of 10 years.

8 POWER SUPPLY UNIT

8.1 General

The power supply unit shall:

- a) The power supply shall be a separate unit contained within its own enclosure
- b) Plug pack power supplies shall not be permitted. Power supply shall be of the in-line type and have the option to be DIN rail mountable. The power supply shall not be hardwired to mains power;
- c) be suitable for connection to nominal 230 VAC 50 Hz earthed-neutral electrical supply, capable of correct operation between 200 V and 265 V a.c.;
- d) provide a regulated DC output voltage to match the nominal input voltage required by the processor board/unit, with a fastening connection compatible with that required by processor board/unit;
- e) be rated at 120% of the maximum power required by the FP when operating with devices connected to all ports;
- f) have a minimum rating of 75% efficiency at 20% full load, or 85% efficiency at 100% full load;
- g) incorporate (or be provided with) adequate transient protection and filtering;
- h) be "safe" in accordance with AS/NZS 3000 and AS/NZS 3100 (e.g. no exposed 230 V contacts, etc); and
- i) provide adequate power to the FP.

9 STANDARDS COMPLIANCE

The device shall pass the following tests and be certified for commercial sale:

- a) Equipment shall comply with the relevant electrical safety requirements specified in AS/NZS 3100. The equipment shall not suffer damage if any of the terminations are open circuited, short circuited or disconnected while energised.
- b) Ethernet ports compliant with Institute of Electrical and Electronics Engineers standard IEEE 802.3
- c) Serial ports compliant with Electronics Industries Association (EIA) standard RS-232-C and/or RS 422 as appropriate.
- d) C-Tick compliance in accordance with AS/NZS 4251.1 (EN 50081.1)

10 SERVICE, WARRANTY, GUARANTEE AND REPAIR

Each Field Processor supplied shall include, as a minimum, a 12-month parts-and-labour warranty (return to base) from the date of delivery.

Spare or replacement components (to the board level) shall be available for purchase from the offerer for a period of at least 12 months following the warranty period (four years is desired).

The supplier shall provide a repair service that allows for FP repairs to be completed within four weeks from delivery to the supplier.

11 PACKAGING AND DELIVERY

The systems shall be supplied fully assembled and packaged individually for shipping.

12 MECHANICAL AND PHYSICAL REQUIREMENTS

12.1 Environmental Conditions

The environmental condition requirements defined in MRTS201 apply to equipment provided under this standard except as described below:

- a) The field processor shall be capable of continuous operation in field cabinets where the ambient temperature is in the range -10 to +80°C and humidity is in the range 0-90% (non-condensing); and

- b) The power supply for the field processor shall be capable of continuous operation in field cabinets where the ambient temperature, as a minimum, is in the range -10 to +65°C and humidity is in the range 0-90% (non-condensing).

13 INSTALLATION REQUIREMENTS

The installation requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.

In addition, the FP and power supply shall be suitable for DIN rail mounting within a telecommunications field cabinets that comply with MRTS201, or traffic signal controller cabinets.

14 ELECTRICAL

The electrical requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.

15 TESTING AND COMMISSIONING

The testing and commissioning requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.

16 DOCUMENTATION

The documentation requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.

In addition, the following documents shall be provided to the Administrator and Transmax Pty Ltd prior to obtaining the STREAMS Compliance certificate:

- An electronic copy of engineering hardware documentation;
- An electronic copy of Technical and User Manuals; and
- An electronic copy of all certification documentation.

17 TRAINING

The training requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.

18 MAINTENANCE

The maintenance requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.

19 HANDOVER

The handover requirements defined in MRTS201 and the Annexure MRTS232.1 apply to equipment provided under this standard.