

Technical Specification

**Transport and Main Roads Specifications
MRTS93 Traffic Signals**

October 2017

Copyright



<http://creativecommons.org/licenses/by/3.0/au/>

© State of Queensland (Department of Transport and Main Roads) 2017

Feedback: Please send your feedback regarding this document to: tmr.techdocs@tmr.qld.gov.au

Contents

- 1 Introduction1**
- 2 Definition of terms1**
- 3 Referenced documents1**
 - 3.1 Standards..... 1
 - 3.2 Standard Drawings 2
- 4 Quality system requirements3**
 - 4.1 Hold Points, Witness Points and Milestones 3
 - 4.2 Construction procedures..... 4
- 5 Compliance with electrical legislation.....4**
- 6 Materials and equipment.....4**
 - 6.1 General 4
 - 6.2 Traffic signal equipment..... 5
 - 6.3 Road lighting equipment 5
 - 6.4 Junction boxes 5
 - 6.5 Terminal panels 5
 - 6.6 Conduits..... 5
 - 6.7 Cement mortar 5
- 7 Design by the Contractor5**
 - 7.1 Submission of design..... 5
 - 7.2 Design changes during construction 6
 - 7.3 Electricity entity 6
- 8 Installation of posts, poles and mast arms.....6**
 - 8.1 General 6
 - 8.2 Traffic signal posts..... 6
 - 8.3 Traffic signal mast arms..... 6
 - 8.4 Traffic signal combination mast arms with road lighting extensions..... 7
 - 8.5 Joint use traffic signal and road lighting poles..... 7
- 9 Installation of lanterns8**
 - 9.1 General 8
 - 9.2 Mounting height 8
 - 9.3 Lantern mounting straps 8
 - 9.4 Lantern cables 8
 - 9.5 Target boards..... 8
 - 9.6 Aiming of lanterns 8
- 10 Installation of pedestrian push buttons9**
 - 10.1 General 9
 - 10.2 Mounting height 9

10.3 Cables.....	9
10.4 Orientation	9
10.5 Audio-tactile drive units.....	9
11 Installation of vehicle detector loops	9
11.1 General	9
11.2 Loop configuration	9
11.3 Installation of loop.....	9
11.4 Conduit.....	9
11.5 Pits	10
11.6 Jointing of cable	10
12 Installation of traffic signal controller	10
12.1 New controller	10
12.2 Modification to existing controller.....	10
12.3 Supply and installation of personality EPROM.....	10
13 Installation of cables	11
13.1 Internal cables.....	11
13.2 External cables	11
13.3 Terminations	11
14 Mains connection.....	11
15 Removal of existing equipment.....	11
15.1 Items to be salvaged.....	11
15.1.1 List of existing items to be salvaged.....	11
15.1.2 Location of storage site	11
15.1.3 Dismantling and storage.....	12
15.2 Items to be demolished.....	12
15.2.1 List of existing items to be demolished.....	12
15.2.2 Demolishing and disposing of materials.....	12
16 Compliance testing.....	12
16.1 Testing procedure	12
16.2 Testing requirements	12
17 Supplementary requirements	13

1 Introduction

This Technical Specification applies to the supply and installation of traffic signals hardware, associated control equipment and cabling.

This Technical Specification shall be read in conjunction with MRTS01 *Introduction to Technical Specifications*, MRTS50 *Specific Quality System Requirements* and other Technical Specifications as appropriate.

This Technical Specification forms part of the Transport and Main Roads Specifications Manual.

2 Definition of terms

The terms used in this Technical Specification shall be as defined in Clause 2 of MRTS01 *Introduction to Technical Specifications*. Further definitions are referenced in Table 2 and AS/NZS 3000. All referenced documents or legislation shall be the latest published or proclaimed version or revision.

Table 2 – Definition of terms

Term	Definition
Act	<i>Electrical Safety Act 2002</i> and associated regulations and codes of practice.
Administrator	Principal's Representative or Superintendent as stated in Clause 14 of MRTS01.
Electrical engineer	Electrical engineer as defined by Schedule 2 of the Act, who has experience in the scope of this Technical Specification as listed in the Transport and Main Roads Core Competency Skills.
Electrical works	As defined in the Act.
Electricity entity	As defined in the Act.
EPROM	Erasable Programmable Read-Only Memory
Licensed electrical contractor	Holder of an Electrical Contractor License under the Act.
MRTS	Transport and Main Roads Technical Specification.
Pit	A wiring enclosure used to provide space for placing and joining cables, pulling cables, performing an operation on cables or for the inclusion of other equipment.
RPEQ	Electrical Engineer who is also a Registered Professional Engineer of Queensland as defined by the <i>Professional Engineers Act of Queensland</i> .
URD	Underground Residential Development as defined by the electricity entity.
Wiring rules	AS/NZS 3000 and / or AS/ACIF S009 as appropriate to the respective service.

3 Referenced documents

3.1 Standards

Table 3.1 lists documents referenced in this Technical Specification or relevant to the design, construction, maintenance and operation of traffic signals. All MRTS documents referenced in this Technical Specification or relevant to the design, construction, maintenance and operation of traffic signals may be accessed from the department's website.

Table 3.1 – Referenced documents

Reference	Title
AS 2339	<i>Traffic signal posts and attachments</i>
AS/NZS 3000	<i>Electrical Installations (known as the Australian / New Zealand Wiring Rules)</i>
DDPSM Vol 2	<i>Drafting and Design Presentation Standards Manual, Volume 2</i>
MRTS01	<i>Introduction to Technical Specifications</i>
MRTS04	<i>General Earthworks</i>
MRTS21	<i>Bituminous Emulsion</i>
MRTS50	<i>Specific Quality System Requirements</i>
MRTS78	<i>Fabrication of Structural Steelwork</i>
MRTS91	<i>Conduits and Pits</i>
MRTS94	<i>Road Lighting</i>
MRTS97	<i>Mounting Structures for Roadside Equipment</i>
MRTS210	<i>Provision of Mains Power</i>
MRTS211	<i>Pedestrian Push Buttons and Audio Tactile Drivers</i>
MRTS228	<i>Electrical Switchboards</i>
MRTS253	<i>Traffic Signal Lanterns</i>
MRTS256	<i>Power Cables</i>
MRTS257	<i>Feeder Cable and Loop Cable for Vehicle Detector</i>
MUTCD	<i>Queensland Manual of Uniform Traffic Control Devices, published by Transport and Main Roads</i>
RPDM	<i>Road Planning and Design Manual, published by Transport and Main Roads</i>
TRUM	<i>Traffic and Road Use Management Manual, published by Transport and Main Roads</i>

3.2 Standard Drawings

All Standard Drawings referenced in this document or relevant to the design, construction, maintenance and operation of traffic signals may be accessed from the department's website.

Table 3.2 – Referenced Standard Drawings

Standard Drawing Number	Title
1323	<i>Road lighting – Luminaire terminal panel</i>
1377	<i>Traffic signals/Road lighting – Joint use traffic signal and road lighting pole</i>
1396	<i>Traffic signals/Road lighting – Joint use traffic signal and road lighting pole and footing installation details</i>
1399	<i>Road lighting – Base plate mounted pole wiring details</i>
1407	<i>Traffic signals – Traffic signal terminal panel for joint use poles</i>
1408	<i>Traffic signals – Traffic signal terminal panel for joint use poles wiring details</i>
1411	<i>Road lighting – Mast arm road lighting junction box (type B)</i>
1412	<i>Road lighting – Mast arm road lighting junction box (type B) wiring details</i>

Standard Drawing Number	Title
1413	<i>Traffic signals – Mast arm traffic signal junction box (type A)</i>
1414	<i>Traffic signals – Mast arm traffic signal junction box (type A) wiring details</i>
1420	<i>Traffic signals – General arrangements</i>
1424	<i>Traffic signals - Detector loops formed insitu in asphalt installation details</i>
1425	<i>Traffic signals – Detector loops placement details</i>
1427	<i>Traffic signals/Road lighting – Mast arm (U series) installation details</i>
1428	<i>Traffic signals – Traffic signal post base mounted</i>
1437	<i>Traffic signals - Hinged base plate for traffic signal post fabrication details</i>
1439	<i>Traffic signals – Traffic signal lantern designations, functions and aiming</i>
1624	<i>Road lighting – Junction box single phase wiring details</i>
1625	<i>Road lighting – Junction box three phase wiring details</i>
1677	<i>Traffic signals/Road lighting – Joint use pole/combination mast arm electrical wiring schematic rate-3</i>
1701	<i>Traffic signals - Detector loops counting/right turn loops and diode connection details</i>
1702	<i>Traffic Signals - Detector loops motorways and ramp placement, and installation details</i>
1782	<i>ITS IPRT network – Typical traffic controller with Telstra modem and associated Next G antenna</i>
1783	<i>ITS IPRT network – Typical traffic controller with tophat Telstra modem and associated Next G antenna</i>

Standard Drawing 1700 and 1704 are withdrawn after being reviewed for currency. Standard Drawing 1703 is withdrawn. Content regarding 'Typical lane setup Lane Red Connections' has been included in Standard Drawing 1425.

4 Quality system requirements

4.1 Hold Points, Witness Points and Milestones

General requirements for Hold Points, Witness Points and Milestones are specified in Clause 5.2 of MRTS01 *Introduction to Technical Specifications*.

The Hold Points, Witness Points and Milestones applicable to this Technical Specification are summarised in Table 4.1.

Table 4.1 – Hold Points, Witness Points and Milestones

Clause	Hold Point	Witness Point	Milestone
7.1	1. Approval of Design for each lot of traffic signal work	1. Certified by a RPEQ	Submission of designs (28 days)
7.2	2. Changes to approved design		

Clause	Hold Point	Witness Point	Milestone
11.3		2. Cutting slots for detector loops	
12.2		3. Modification to controller	
12.3		4. EPROM personality verification	
13.2		5. Cable laying	
14		6. Mains power connection	
15.1.1	3. Salvage of items of traffic signal equipment		Submission of schedule of items to be salvaged (seven days)
15.1.3	4. Approval prior to removal of items to be salvaged which cause damage		
16.1	5. Commencement of compliance testing		Submission of compliance testing procedure (28 days)
16.2	6. Compliance testing		

4.2 Construction procedures

Construction procedures which are required to be submitted in accordance with Clause 1 of MRTS50 *Specific Quality System Requirements* are listed in Table 4.2.

Table 4.2 – Construction procedures

Clause	Procedure
12.2	Modification of controller
13.2	Laying of cables
15.1	Removal, transport and storage of existing equipment to be salvaged
16	Compliance testing

5 Compliance with electrical legislation

The work covered by this Technical Specification shall comply with the requirements of the Act and subordinate legislation and AS/NZS 3000.

A licensed electrical contractor shall be engaged to perform the duties and functions of 'electrical works' as defined in the Act.

An electrical engineer shall be engaged to perform the duties of design work within the scope of this Technical Specification.

6 Materials and equipment

6.1 General

All materials shall comply with the requirements of this Technical Specification and the details shown on the Standard Drawings nominated herein and / or the drawings on the Transport and Main Roads website.

For traffic signal installations only, approved products shall be used. For structural items, refer to MRTS78 *Fabrication of Structural Steelwork* and the relevant Standard Drawings.

For traffic signal equipment, refer to ITS & Electrical Technology Branch; type approved products.

6.2 Traffic signal equipment

Equipment shall be supplied and manufactured in accordance with the requirements of MRTS78 *Fabrication of Structural Steelwork*, MRTS97 *Mounting Structures for Roadside Equipment*, MRTS211 *Pedestrian Push Buttons and Audio Tactile Drivers*, MRTS253 *Traffic Signal Lanterns*, MRTS255 *Traffic Signal Controllers*, MRTS256 *Power Cables*, and MRTS257 *Feeder Cable and Loop Cable for Vehicle Detector*.

6.3 Road lighting equipment

Road lighting components not specifically described in this Technical Specification shall comply with the requirements of MRTS94 *Road Lighting*.

6.4 Junction boxes

Column-mounted traffic signal junction boxes shall comply with the details shown on Standard Drawing 1413. Column-mounted road lighting junction boxes shall comply with details shown on Standard Drawing 1411.

Road lighting junction boxes installed in pits for joint use poles or combination mast arms shall comply with the details shown on Standard Drawing 1624 (for single phase supply) and 1625 (for three-phase supply).

6.5 Terminal panels

Terminal panels for installation in joint use traffic signal and road lighting poles shall comply with the details shown on the following Standard Drawings:

- a) Traffic signal terminal panels – Standard Drawing 1407, and
- b) Road lighting terminal panels – Standard Drawing 1323.

6.6 Conduits

Corrugated conduit shall not be used for trenched or traffic signal installations. Heavy duty corrugated or Core-flow™ conduit types are also excluded from traffic signal installations.

6.7 Cement mortar

Cement mortar shall consist of one part of Type GP cement and three parts of clean sharp sand, with just sufficient water added to form a moist mortar suitable for dry packing.

7 Design by the Contractor

7.1 Submission of design

Where design of the traffic signal installation is undertaken by the Contractor, the requirements of Clause 7 shall apply.

Not less than 28 days prior to the proposed installation of traffic signal equipment, lanterns and / or poles, the Contractor shall submit to the Administrator, a traffic signal design which complies with the requirements of the RPDM, this Technical Specification and relevant Standard Drawings. **Milestone**

The design shall be submitted in accordance with the provisions of the Contract governing design by the Contractor. As a guidance note, if the Contractor chooses to divide the work into lots as per MRTS50 *Specific Quality System Requirements*, then it is recommended that all of the traffic signal equipment at each intersection be considered as one lot. Generally, the MRTS91 *Conduits and Pits*, MRTS94 *Road Lighting* or MRTS228 *Electrical Switchboards* and MRTS256 *Power Cables* guidance would say each lot should include all equipment connected to each electrical switch board.

The design shall be certified by a person experienced in traffic signal design and holding a current registration as a Registered Professional Engineer, Queensland. **Witness Point 1**

Construction under this Technical Specification shall not commence until approval is granted by the department or as otherwise provided for by the Contract. **Hold Point 1**

7.2 Design changes during construction

Any change to the design of any component proposed during construction shall be subject to the provisions of Clause 7 and referred to the engineer responsible for the original design. Only after all the requirements of this Technical Specification have been satisfied, shall such changes be incorporated in the Works. **Hold Point 2**

7.3 Electricity entity

As part of the design requirement, the provision of new traffic signal installations and the removal or relocation of existing traffic signal equipment shall require advice to be provided to the electricity entity. Such advice shall include at least a record of the location (e.g. suburb), wattage and pole number of all traffic signal poles. A copy of such advice shall be included in the quality records.

8 Installation of posts, poles and mast arms

8.1 General

Installation of traffic signal posts, traffic signal mast arms and joint-use traffic signals and road lighting poles shall comply with the requirements of the details shown in the drawings and / or the relevant Standard Drawings.

Care shall be taken to ensure that any openings for cables, junction boxes, push buttons or outreach are correctly aligned when assembling and installing components.

8.2 Traffic signal posts

The general installation requirements for traffic signal posts are shown on Standard Drawing 1428.

The location and length of traffic signal posts shall be as shown in the Drawings.

Posts shall be installed on the holding down bolts at the appropriate level. Before tightening the nuts, posts shall be set vertical by adjustment of the levelling nuts.

Where shown in the drawings, a hinged base plate complying with the details shown on Standard Drawing 1437 shall be installed.

8.3 Traffic signal mast arms

The general installation requirements for traffic signal mast arms are shown on Standard Drawing 1427.

A traffic signal junction box shall be installed on the pole in accordance with Standard Drawing 1414.

The location, outreach length and orientation of traffic signal mast arms shall be as shown in the drawings.

The mast arm outreach may be pre-assembled to the mast arm column or may be installed after erection of the mast arm column. The joint between the mast arm column and the outreach shall be sealed with an appropriate silicone sealant, which shall not damage the galvanised coating.

Mast arm columns shall be installed on the holding-down bolts at the appropriate level with the column set vertical.

The outreach lantern cable shall be installed in the mast arm assembly and terminated at each end.

Where the mast arm has a road lighting luminaire spigot which is not to be used immediately, the spigot cap shall be installed on the spigot and sealed with an appropriate silicone sealant which shall not damage the galvanised coating.

After all traffic signal lanterns have been fitted to the mast arm column and outreach, the rake of the column shall be adjusted to provide the most pleasing aesthetic appearance from a distance in any direction without affecting the visibility of the traffic signal lanterns. This may need to be a compromise due to deflection in the column and outreach.

When the mast arm is in the correct location the space between the underside of the base plate and the top of the footing shall be packed with dry cement mortar. The edges of the mortar shall be finished in accordance with the details shown on Standard Drawing 1427.

8.4 Traffic signal combination mast arms with road lighting extensions

Where shown in the drawings, a road lighting installation shall be included with the traffic signal mast arm. The electrical installation shall comply with Standard Drawing 1412 for the road lighting connections and Standard Drawing 1414 for the traffic signal connections. The electrical wiring schematic for traffic signal combination mast arms with road lighting extensions is shown in Standard Drawing 1677.

Where this is the case, the traffic signal mast arm column shall include a road lighting spigot. A road lighting transition piece shall be installed on the spigot and a road lighting junction box shall be fixed to the column at the location shown on Standard Drawing 1427.

The road lighting luminaire cable shall be installed from the pit to the open end of the luminaire transition piece.

The remainder of the road lighting components shall be supplied and installed in accordance with the requirements of MRTS94 *Road Lighting*.

8.5 Joint use traffic signal and road lighting poles

The general installation requirements for joint use traffic signal and road lighting poles are shown on Standard Drawing 1377. The electrical wiring schematic for joint use traffic signal and road lighting poles is shown in Standard Drawing 1677.

The location of joint use traffic signal and road lighting poles shall be as shown in the drawings.

Poles shall be installed on the holding down bolts at the appropriate level. Before tightening the nuts, poles shall be set vertical by adjustment of the levelling nuts.

When the pole is in the correct location the space between the underside of the base plate and the top of the footing shall be packed with dry cement mortar. The edges of the mortar shall be finished in accordance with the details shown on Standard Drawing 1396.

The traffic signal and road lighting terminal panels shall be installed on the pole in accordance with Standard Drawing 1399 for road lighting connections and Standard Drawing 1408 for the traffic signal connections.

The traffic signal and road lighting terminal panels shall be installed in the pole at the appropriate locations.

The road lighting supply cable shall be installed from the road lighting pit to the road lighting terminal panel and the luminaire cable shall be installed from the terminal panel to the upper end of the pole. An appropriate junction box shall be installed in the road lighting pit.

The remainder of the road lighting components shall be supplied and installed in accordance with the requirements of MRTS94 *Road Lighting*.

9 Installation of lanterns

9.1 General

Traffic signal vehicle lanterns and pedestrian lanterns shall be installed with relevant accessories as shown in the drawings or as otherwise specified in this Technical Specification.

9.2 Mounting height

Mounting heights for traffic signal vehicle lanterns and pedestrian lanterns shall be as shown in the drawings. Minimum clearance to outreach mounted vehicle lanterns as shown on Standard Drawing 1420 shall be maintained.

9.3 Lantern mounting straps

Lantern mounting straps shall be supplied and installed in accordance with the requirements of AS 2339.

Where standard straps provided with lanterns are not of a suitable length, they shall be replaced with straps of the required length.

9.4 Lantern cables

Lantern cables shall be installed through appropriate access holes in the support structure and shall be terminated at the appropriate traffic signal terminal panel in accordance with the wiring details shown in the drawings.

9.5 Target boards

Appropriately-sized target boards shall be attached to traffic signal vehicle lanterns using the attaching devices supplied.

9.6 Aiming of lanterns

All lanterns shall be appropriately aimed relative to their function and approach speed as per Standard Drawing 1439.

10 Installation of pedestrian push buttons

10.1 General

Pedestrian push buttons shall be installed with relevant accessories as shown in the drawings or as otherwise specified in this Technical Specification.

10.2 Mounting height

Mounting heights for pedestrian push button assemblies shall be as shown in the drawings.

10.3 Cables

Cables from pedestrian push buttons shall be installed through appropriate access holes in the support structure and shall be terminated at the appropriate traffic signal terminal panel in accordance with the wiring details shown in the drawings.

10.4 Orientation

Pedestrian push buttons shall be oriented so that the face of the buttons is parallel to the applicable crosswalk with the face of the buttons on the side on which pedestrians normally walk.

10.5 Audio-tactile drive units

Where required by the details shown in the drawings, audio-tactile driver units shall be installed in the appropriate location on the face of the support post, column or pole.

11 Installation of vehicle detector loops

11.1 General

Vehicle detector loops shall be installed in the locations shown in the drawings with the assistance, where necessary, of Standard Drawing 1425.

11.2 Loop configuration

Loop configurations shall be as shown in the drawings.

11.3 Installation of loop

Vehicle detector loops must be installed as per the department's Standard Drawings 1424, 1425, 1701 and 1702 and MRTS21.

The installation of detector loops is outlined in Standard Drawing 1424 and 1702.

Any sharp edges in the slot which might damage the detector loop cable during installation shall be smoothed off. The slot shall be cleaned out using dry compressed air. **Witness Point 2**

The detector loop cable shall be installed in the slot in a single continuous length and wound with the number of loops stated in the drawings. Both ends of the cable shall terminate in the jointing pit.

11.4 Conduit

A 25 mm nominal diameter conduit shall be installed from the edge of the pavement to the jointing pit in accordance with the requirements of MRTS91 *Conduits and Pits*.

11.5 Pits

Unless otherwise shown in the drawings, vehicle detector loop pits shall be installed against the kerb or on the pole alignment as appropriate. Pits shall conform to the requirements of MRTS91 *Conduits and Pits*.

11.6 Jointing of cable

The ends of the detector loop cable shall be connected to the detector feed cable in the jointing pit using appropriate epoxy jointing kits.

12 Installation of traffic signal controller

12.1 New controller

Traffic signal controllers shall be installed in the locations shown in the drawings.

The controller shall be positioned on the concrete base and the nuts on the holding down bolts tightened securely.

Where the controller is installed adjacent to the kerb, it shall be oriented such that the door opens on the opposite side of the controller to the carriageway.

Where wireless communication equipment are installed in the controller, the modem and associated antenna shall be installed in accordance with Standard Drawing 1782 and 1783. Any holes made, by drilling or otherwise, on the controller enclosure for installation of the antenna, shall be sealed such that the IP rating of the enclosure is not compromised.

This requirement is to ensure the proper installation of antennas for wireless communication in accordance with Standard Drawing 1782 and 1783.

An effective earthing electrode shall be installed at the controller in an adjacent pit and shall be connected to the installation earthing terminal.

12.2 Modification to existing controller

Where so stated in Clause 2 of Annexure MRTS93.1, existing traffic signal controllers shall be modified in accordance with the requirements stated in Clause 2 of Annexure MRTS93.1. Such modification may include:

- a) the supply and installation of additional components
- b) the removal of existing components, and
- c) re-programming of the EPROM.

All modifications to existing traffic signal controllers shall be completed prior to commencement of testing of the installation. **Witness Point 3**

12.3 Supply and installation of personality EPROM

A certificate verifying the functionality of personality EPROM modules shall be submitted to the Administrator prior to commencement of testing of any traffic signal installation. **Witness Point 4**

13 Installation of cables

13.1 Internal cables

Cables from a traffic signal terminal assembly to pedestrian lanterns and pedestrian push buttons shall be installed in accordance with the requirements of AS/NZS 3000.

Internal cables for road lighting installations shall be carried out in accordance with the requirements of MRTS94 *Road Lighting*.

13.2 External cables

Cables between a traffic signal controller and:

- a) the terminal assembly of traffic signal posts, mast arms and joint use poles, and
- b) vehicle detector loops

shall be installed in accordance with the requirements of AS/NZS 3000 and MRTS228 *Electrical Switchboards* and MRTS256 *Power Cables* without intermediate joints. **Witness Point 5**

A minimum of six metres of slack multi-core cable shall be coiled in each pit adjacent to traffic signal controllers, posts, mast arms and joint use poles, and two metres in all intermediate pits.

13.3 Terminations

Terminal connections of traffic signal cables shall be carried out as shown in the drawings.

All unused cores in cables shall be terminated at spare terminals at traffic signal posts, mast arms and joint use poles. Unused cores shall be terminated on an earth bar at the traffic signal controller. This earth bar shall be bonded to the main earth bar.

14 Mains connection

Where shown in the drawings, a mains connection cable shall be installed to an appropriate pole-mounted mains connection box or pillar-mounted switchboard in accordance with the requirements of MRTS228 *Electrical Switchboards* and MRTS256 *Power Cables*. **Witness Point 6** Where specified in the drawings, mains power shall be provided to the site in accordance with MRTS210 *Provision of Mains Power*

15 Removal of existing equipment

15.1 Items to be salvaged

15.1.1 List of existing items to be salvaged

Any items of existing equipment to be dismantled and salvaged are listed in Clause 1.1 of Annexure MRTS93.1.

Not less than seven days prior to commencement of dismantling and removal of any existing traffic signal equipment, the Contractor shall submit a schedule of items of existing traffic signal equipment to be dismantled for re-erection in accordance with the drawings. **Milestone**

Dismantling and removal shall not commence until expiration of the seven day period. **Hold Point 3**

15.1.2 Location of storage site

Salvaged items shall be transported to the storage site nominated in Clause 1.2 of Annexure MRTS93.1.

15.1.3 Dismantling and storage

Existing traffic signal equipment to be salvaged shall be dismantled and removed with minimum damage to the items.

Where possible, fittings shall be undone, components disassembled and supports removed without any damage and / or cutting of the components. Where this is not possible, Administrator's approval shall be obtained for any procedure which may cause damage. **Hold Point 4**

Salvaged materials shall be carefully transported to the storage site nominated in Clause 15.1.2.

Salvaged materials shall be neatly stacked at the storage site on appropriate timber packers.

15.2 Items to be demolished

15.2.1 List of existing items to be demolished

The items of existing equipment to be demolished and disposed of are listed in Clause 3 of Annexure MRTS93.1.

Additionally, any footings and bases associated with equipment to be salvaged as defined in Clause 15.1.1 shall be demolished and disposed of.

15.2.2 Demolishing and disposing of materials

Nominated existing traffic signal equipment shall be demolished and removed in a manner which avoids damage to any adjacent items.

All existing footings shall be removed. Resulting excavations shall be backfilled and finished so as to reinstate the area to a safe and free draining state. Backfilling shall be carried out in accordance with the requirements of MRTS04 *General Earthworks*. The surface shall be reinstated with material matching the surrounding area.

Demolished equipment and debris shall be disposed of in accordance with the requirements of Clause 11 of MRTS01 *Introduction to Technical Specifications*.

16 Compliance testing

16.1 Testing procedure

Not less than 28 days prior to commencement of testing of traffic signal equipment, the Contractor shall submit to the Administrator its compliance testing procedure. **Milestone**

Compliance testing shall not commence until expiration of the 28 day period. **Hold Point 5**

16.2 Testing requirements

The Contractor is responsible for carrying out sufficient testing to ensure that materials and construction standards comply with this Technical Specification and the requirements of the Act. Electrical tests shall include at least the mandatory tests detailed in AS/NZS 3000 and earth fault loop impedance tests.

In addition, before commissioning, the following compliance tests shall be carried out:

- a) isolation and resistance test, testing of lanterns, flash test, loop continuity and numbering test, push button conductivity and numbering and controller connections to mains power, and
- b) phase and timing testing of the installation.

Compliance testing shall be carried out in the presence of the Administrator. **Hold Point 6**

The following documents shall be included in the quality records:

- a) a Certificate of Test and Compliance
- b) a Record of Inspection and Tests, and
- c) accurate As Constructed Drawings.

17 Supplementary requirements

The requirements of MRTS93 *Traffic Signals* are varied by the supplementary requirements given in Clause 4 of Annexure MRTS93.1.

