

**Specification (Measurement)**

**Transport and Main Roads Specifications  
MRS12 Sprayed Bituminous Emulsion Surfacing**

**November 2018**

## Copyright

© The State of Queensland (Department of Transport and Main Roads) 2018.

## Licence



This work is licensed by the State of Queensland (Department of Transport and Main Roads) under a Creative Commons Attribution (CC BY) 4.0 International licence.

## CC BY licence summary statement

In essence, you are free to copy, communicate and adapt this work, as long as you attribute the work to the State of Queensland (Department of Transport and Main Roads). To view a copy of this licence, visit: <https://creativecommons.org/licenses/by/4.0/>

## Translating and interpreting assistance



The Queensland Government is committed to providing accessible services to Queenslanders from all cultural and linguistic backgrounds. If you have difficulty understanding this publication and need a translator, please call the Translating and Interpreting Service (TIS National) on 13 14 50 and ask them to telephone the Queensland Department of Transport and Main Roads on 13 74 68.

## Disclaimer

While every care has been taken in preparing this publication, the State of Queensland accepts no responsibility for decisions or actions taken as a result of any data, information, statement or advice, expressed or implied, contained within. To the best of our knowledge, the content was correct at the time of publishing.

## Feedback

Please send your feedback regarding this document to: [tmr.techdocs@tmr.qld.gov.au](mailto:tmr.techdocs@tmr.qld.gov.au)

**Contents**

- 1 Introduction .....1**
- 2 Measurement of works .....1**
  - 2.1 Standard Work Items ..... 1
  - 2.2 Work Operations ..... 1
    - 2.2.1 *Methods of quantifying sprayed bituminous emulsion surfacing*.....3
    - 2.2.2 *Calculation of quantities* .....5
  - 2.3 Principal’s materials ..... 5
    - 2.3.1 *Return of excess Principal’s materials and / or containers* .....5
    - 2.3.2 *Takeover of excess Principal’s bituminous emulsion (excluding modified bituminous emulsion)* 5
    - 2.3.3 *Additional Principal’s materials used to rectify a rejected lot* .....6
  - 2.4 Utilisation of a rejected lot for a reduced level of service ..... 6
    - 2.4.1 *Maximum reductions in standards*.....6
    - 2.4.2 *Determination of the reduced value* .....6
  - 2.5 Multiple reduction ..... 7

## 1 Introduction

This Specification applies to the application of sprayed bituminous emulsion surfacing. The work covered includes primes, primerseals, seals, reseals and enrichments.

This Specification shall be read in conjunction with MRS01 *Introduction to Specifications* and other Specifications as appropriate.

This Specification forms part of the Transport and Main Roads Specifications Manual.

## 2 Measurement of works

### 2.1 Standard Work Items

In accordance with the provisions of Clause 2.1.3 of MRS01 *Introduction to Specifications*, the standard work items covered by this Specification are listed in Table 2.1.

**Table 2.1 – Standard Work Items**

Standard Item No.	Description	Unit of Measurement
<b>Sprayed Bituminous Emulsion Surfacing</b>		
40801	Prime, grade [grade], spray rate [spray rate], [including   excluding] supply of binder, [location]	litre
40802	Primerseal, grade [grade], spray rate [spray rate], [including   excluding] supply of binder, [location]	litre
40803	Seal, grade [grade], spray rate [spray rate], [including   excluding] supply of binder, [location]	litre
40804	Reseal, grade [grade], spray rate [spray rate], [including   excluding] supply of binder, [location]	litre
40805	Enrichment, grade [grade], spray rate [spray rate], [including   excluding] supply of binder, [location]	litre
40806	Spreading prime cover material [material], [spread rate], [location]	m <sup>3</sup>
40807	Spreading cover aggregate [size], [spread rate], [location]	m <sup>3</sup>
40808	Supply of bituminous emulsion [material], [class   grade]	litre
40809	Transport of bituminous emulsion supplied by the Principal [material], from [supply location]	litre
40810	Transport of aggregate supplied by the Principal [material], from [supply location]	m <sup>3</sup>
40811	Sprayed bituminous emulsion surfacing, [including   excluding] supply of binder, [including   excluding] supply of cover aggregates, [location], refer to Clause 1 of Annexure MRS12.1	m <sup>2</sup>

### 2.2 Work Operations

**Item 40801** Prime, grade [grade], spray rate [spray rate], [including | excluding] supply of binder, [location]

**Item 40802** Primerseal, grade [grade], spray rate [spray rate], [including | excluding] supply of binder, [location]

**Item 40803 Seal, grade [*grade*], spray rate [*spray rate*], [*including* | *excluding*] supply of binder, [*location*]**

**Item 40804 Reseal, grade [*grade*], spray rate [*spray rate*], [*including* | *excluding*] supply of binder, [*location*]**

**Item 40805 Enrichment, grade [*grade*], spray rate [*spray rate*], [*including* | *excluding*] supply of binder, [*location*]**

Work Operations incorporated in the above items include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) preparation of the surface prior to spraying
- c) supply of binder, where stated
- d) loading materials into the sprayer
- e) incorporating, mixing and heating materials, as relevant
- f) spraying
- g) unloading materials from the sprayer, if necessary, and
- h) cleaning roadside items, if necessary.

**Item 40806 Spreading prime cover material [*material*], [*spread rate*], [*location*]**

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) loading, hauling, spreading, drag brooming and rolling of material, and
- c) removal and disposal of excess material.

**Item 40807 Spreading cover aggregate [*size*], [*spread rate*], [*location*]**

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) loading, hauling, spreading, drag brooming and rolling of material, and
- c) removal and disposal of excess material.

**Item 40808 Supply of bituminous emulsion [*material*], [*class* | *grade*]**

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) supply of material
- c) transport and storage of material, and
- d) removal of excess material from the Site.

**Item 40809**      **Transport of bituminous emulsion supplied by the Principal [material], from [supply location]**

**Item 40810**      **Transport of aggregate supplied by the Principal [material], from [supply location]**

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) transport of material from the point of supply by the Principal to the Site as set out in the Principal Supplied Material List (Form C6827), and
- c) storage of material.

**Item 40811**      **Sprayed bituminous emulsion surfacing, [including | excluding] supply of binder, [including | excluding] supply of cover aggregates, [location], refer to Clause 1 of Annexure MRS12.1**

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) supply of all material, including binder, additives, prime cover material and cover aggregates, other than that supplied by the Principal as stated on Form C6827
- c) transport and storage of material
- d) preparation prior to spraying
- e) loading the relevant materials into the sprayer
- f) incorporating, mixing and heating materials, as relevant
- g) spraying
- h) unloading materials from the sprayer, if necessary
- i) cleaning roadside items, if necessary
- j) loading, hauling, spreading of prime cover material and cover aggregate
- k) drag brooming and rolling of cover aggregate
- l) removal and disposal of excess prime cover material and cover aggregate, and
- m) removal of excess material from the Site.

## **2.2.1 Methods of quantifying sprayed bituminous emulsion surfacing**

### **2.2.1.1 General**

Two methods are used for quantifying the work associated with sprayed bituminous emulsion surfacing. They are:

- a) by measuring the quantities of materials used in the surfacing operation, and
- b) by measuring the required area of surfacing.

### 2.2.1.2 Quantifying by materials used

This method provides for the separate measurement of a spraying operation and a spreading operation.

The spraying operation shall be measured by Work Items 40801 (prime), 40802 (primerseal), 40803 (seal), 40804 (reseal) and 40805 (enrichment) which can either include or exclude the supply of binder. The following shall apply to quantifying the spraying operation:

- a) where the supply of binder is included, the Work Item shall be deemed to include all binder materials, and
- b) where the supply of binder and / or additives is excluded, bituminous material can be supplied by either the Principal or the Contractor. Material to be supplied by the Principal will be as listed on the Principal Supplied Material List (Form C6827). Any material not listed on the Principal Supplied Material List shall be supplied by the Contractor. Additional Work Items shall apply as follows
  - i. where bituminous emulsion materials are to be supplied by the Contractor, Work Item 40808 shall be provided for each grade of bituminous emulsion material so supplied, and
  - ii. where bituminous emulsion materials are to be supplied by the Principal, Work Item 40809 shall be provided for transport from the point of supply of each grade of bituminous emulsion material so supplied.

The spreading operation shall be measured by Work Items 40808 (prime cover material) and 40807 (cover aggregate) which are for spreading of material only. Materials can be supplied by either the Principal or the Contractor. Material to be supplied by the Principal will be as listed on the Principal Supplied Material List (Form C6827). Any material not listed on the Principal Supplied Material List shall be supplied by the Contractor.

Where aggregate materials are to be supplied by the Contractor, the Work Items included in MRS22 *Supply of Cover Aggregates* shall apply.

Where aggregate materials are to be supplied by the Principal, Work Item 40810 shall be provided for transport from the point of supply of each type of aggregate material so supplied.

### 2.2.1.3 Quantifying by area

This method provides for the measurement of the complete surfacing operation by the area of surface required to be covered. In this case, only Work Item 40811 shall be provided in the Schedule of Rates and it shall be deemed to include the supply and installation of all materials in accordance with this Specification (including bituminous emulsion, prime cover material and cover aggregates).

The details of the surfacing treatment represented by Work Item 40811 shall be as stated in Clause 1 of Annexure MRS12.1.

Where material is to be supplied by the Principal, it will be listed on the Principal Supplied Material List (Form C6827) and Work Item 40809 or 40810 shall be provided for transport from the point of supply of each type of material so supplied. Any material not listed on the Principal Supplied Material List shall be supplied by the Contractor.

## **2.2.2 Calculation of quantities**

### **2.2.2.1 Prime, primerseal, seal, reseal and enrichment**

The quantities of prime, primerseal, seal, reseal, enrichment, at 15°C, shall be determined from the tally of actual quantities of bituminous material sprayed on each spray run, or the quantity calculated from the Designed Spray Rate, whichever is the lesser.

### **2.2.2.2 Spreading prime cover material and cover aggregate**

The quantity of prime cover material and / or cover aggregate spread shall be determined from the tally of quantities of material used on each spray run or the quantity calculated from the Designed Spread Rate, whichever is the lesser.

### **2.2.2.3 Supply of bituminous emulsion**

The quantity of bituminous emulsion measured as residual bitumen, shall be determined at 15°C, from the tally of actual quantities of bituminous emulsion sprayed on each spray run, or the quantity calculated from the Designed Spray Rate, whichever is the lesser.

### **2.2.2.4 Transport of material supplied by the principal**

The quantity for transport of bituminous emulsion supplied by the Principal will be the actual quantity of bituminous emulsion, at 15°C, released to the Contractor at the point of supply.

The quantity for transport of prime cover material and / or cover aggregates supplied by the Principal will be determined from the tally of quantities of material used on each spray run or the quantity calculated from the Designed Spread Rate, whichever is the lesser.

### **2.2.2.5 Sprayed bituminous emulsion surfacing by area**

The quantity of sprayed bituminous emulsion surfacing when specified by area shall be calculated from the actual plan dimensions shown on the drawings.

## **2.3 Principal's materials**

### **2.3.1 Return of excess Principal's materials and / or containers**

Those Principal's materials and / or containers listed as returnable in the Principal Supplied Material List, Form C6827, and which are not used in the Works shall be returned to the Principal at the point of return given in the Principal Supplied Material List.

Payment for the return of excess materials and / or containers shall be at the rate for Transport of Materials (Item 40809), or if not appropriate, then as agreed to by the Superintendent and the Contractor. If an agreement cannot be reached, the Superintendent shall determine a rate based on quotations from a third party for work of a similar nature.

### **2.3.2 Takeover of excess Principal's bituminous emulsion (excluding modified bituminous emulsion)**

Those Principal's materials listed in the Principal Supplied Material List, Form C6827 as materials to be taken over by the Contractor and which are not used in the Works shall be taken over by the Contractor. This Clause does not include prime cover material or cover aggregate.

The takeover value shall be calculated from the quantity of excess material and the purchase unit rate paid by the Principal. The purchase price shall not include any transport and overhead charges.

The takeover value of excess material shall be deducted from the payments made to the Contractor. The deductions shall not affect any other entitlements to the Contractor under this Contract, such as cost adjustment for rise and fall in material costs.

### **2.3.3 Additional Principal's materials used to rectify a rejected lot**

Where a lot has been rejected and the Contractor has to use additional Principal's materials to carry out additional work and / or replace part or all of the lot, the cost of the additional Principal's materials shall be deducted from the payment made to the Contractor.

Where a lot has been rejected but subsequently accepted, the cost of any Principal's materials used on that lot during the original operations and in excess of the limits given in this Specification, shall be deducted from the payment made to the Contractor.

Neither of the above applies to a lot utilised for a reduced level of service.

## **2.4 Utilisation of a rejected lot for a reduced level of service**

### **2.4.1 Maximum reductions in standards**

A lot which has an Actual Spray Rate outside  $\pm 10\%$  of the Designed Spray Rate shall not be accepted for a reduced level of service.

A lot which has an amount of cover aggregate spread outside - 5% or + 10% of the Designed Spread Rate shall not be accepted for a reduced level of service.

The maximum reduction in standards for bituminous emulsion shall be as specified in the Specification for supply of bitumen emulsion.

### **2.4.2 Determination of the reduced value**

#### **2.4.2.1 Bituminous emulsion**

The percentage reduction in value for defects of delivered bituminous emulsion shall be equal to the number of defects determined from Clause 8.4 of MRTS21 *Bituminous Emulsion*. This percentage reduction shall be applied to the rate for prime, primerseal, seal, reseal or enrichment as applicable.

#### **2.4.2.2 Surfacing**

The percentage reductions in value shall apply only to the schedule rate for prime, seal, and reseal, or spreading cover aggregate, as relevant.

The percentage reductions in value shall be as stated in Tables 2.4.2.2(a) and 2.4.2.2(b). The percentage differences in spray rates and spread rates shall be rounded to the nearest whole number.

**Table 2.4.2.2(a) – Reduction in value, spray rate**

<b>% Difference from Designed Spray Rate</b>	<b>% Reduction in Value</b>
± 6	4
± 7	8
± 8	12
± 9	16
± 10	20

**Table 2.4.2.2(b) – Reduction in value, aggregate spread rate**

<b>% Difference</b>		<b>% Reduction in Value</b>
<b>Less Than</b>	<b>Greater Than</b>	
- 1	+ 6	2
- 2	+ 7	4
- 3	+ 8	6
- 4	+ 9	8
- 5	+ 10	10

Note: The percentage difference relates to the amount of material spread calculated from the Design Spread Rate as:

$$\text{Amount Spread} = \frac{1}{\text{Spread Rate}}$$

## **2.5 Multiple reduction**

Where more than one reduction applies, the percentage reductions shall be added.

