

**PIEZO-PIEZO-LOOP-PIEZO-PIEZO
CONFIGURATION
SINGLE CARRIAGEWAY DUAL DIRECTION**

NOTES:


1. The WiM sensor can be either a Brass Linguini (BL) piezo or quartz sensor
2. The WiM sensor is to be assembled and tested prior to delivery at site.
3. All slots for Loop and WiM sensors shall be cut to nearest pit.
4. Where possible, there shall be a minimum 500mm gap between slots cut for sensors and tails.
5. Loops shall be installed centrally between the lane lines.
6. Loop leading and trailing edges shall be perpendicular to the centre line of the road.
7. Loop shoulder and centre line edges shall be parallel to the centre line of the road.
8. WiM sensors shall be installed perpendicular to the centre line of the road.
9. Separation of middle WiM sensors shall be 3000mm ± 3mm, measured at the centre of each sensor.
10. Dimensions are in metres unless noted otherwise.

ASSOCIATED DEPARTMENTAL DOCUMENTS:
Standard Drawings
Specifications


REFERENCED DOCUMENTS:
Departmental Standard Drawings:
1901 ITS - Traffic Monitoring Cabinet Base Installation Details
1905 ITS - Traffic Monitoring Cabinet Typical Details
1906 ITS - WiM Piezo Sensor Installation Details

Departmental Specifications:
MRTS203 Provision of Weigh-in-Motion System
MRTS207 Traffic Monitoring Foundation Equipment
MRTS250 Provision of Automatic Number Plate Recognition System

INSTALLATION OF CONDUITS AND PITS IS THE RESPONSIBILITY OF THE LICENSED ELECTRICAL CONTRACTOR



**PIEZO-PIEZO-LOOP-PIEZO-PIEZO
CONFIGURATION
DUAL CARRIAGEWAY SINGLE DIRECTION
2 LANES**



**PIEZO-PIEZO-LOOP-PIEZO-PIEZO
CONFIGURATION
DUAL CARRIAGEWAY SINGLE DIRECTION
3 LANES**

LEGEND

SYMBOL	DESCRIPTION
	ANPR Camera with pole
	PTZ Dome Camera with pole
	Wireless Antenna
	Field Cabinet
	Type 4 Pit
	Circular Pit
	1x100 dia conduit (White)
	2x100 dia conduit (White)

Department of Transport and Main Roads			
ITS			
WIM SENSOR CONFIGURATION PIEZO-PIEZO-LOOP-PIEZO-PIEZO		A3 Not to Scale	Standard Drawing No 1909 Date 07/19
A	B		