



NOTES:

FLOOD DEPTH INDICATORS:

1. To be located at the chainages specified or as directed by the Superintendent.
2. Zero mark to be set at the lowest pavement level on the section of road subject to flooding.
3. G9-22-2 and G9-22-3 indicators to be erected on progressively higher ground where flood depths are in excess of 1.5m or 3.5m respectively.
4. To conform with the details as shown in the MUTCD.

CONCRETE SURROUND:

5. To be class N20/20 and provide 100mm minimum cover all round.
6. Dimensions are in millimetres unless shown otherwise.

ASSOCIATED DEPARTMENTAL DOCUMENTS:

- Standard Drawings Specifications
- Manual of Uniform Traffic Control Devices (MUTCD)

REFERENCED DOCUMENTS:

- Departmental Specifications:
 MRTS14 Road Furniture
 MRTS70 Concrete

Australian Standards:

- AS1743 Road Signs - Specifications

Department of Transport and Main Roads		 Queensland Government	 <small>© The State of Queensland (Department of Transport and Main Roads) 2014 http://creativecommons.org/licenses/by/3.0/au</small>
FLOOD DEPTH INDICATORS			
INSTALLATION		A3 Not to Scale	Standard Drawing No <h1 style="margin: 0;">1170</h1> Date 6/14
A	B	C	