

**Registered Prestressing Strand****4 December 2023**

Strand is registered in accordance with the Supplier Registration Scheme: Bridges and Other Structures

Registered Product	Supplier	Production Line
AS/NZS 4672.1 – 7 wire ordinary – 12.7 – 1870 – Relax 2 – Right	Siam Industrial Wire	KM2
AS/NZS 4672.1 – 7 wire ordinary – 15.2 – 1830 – Relax 2 – Right	Siam Industrial Wire	KM2
AS/NZS 4672.1 – 7 wire ordinary – 12.7 – 1870 – Relax 2 – Right	Silvery Dragon	1
AS/NZS 4672.1 – 7 wire ordinary – 15.2 – 1830 – Relax 2 – Right	Silvery Dragon	3

*Note that 15.2 mm strand with nominal tensile strength of 1830 MPa, or 15.2 mm with nominal tensile strength of 1860 MPa strand may be used in place of 15.2 mm 1750 MPa strand without seeking designer approval using the same minimum design jacking force.*

*Note that 15.2 mm strand with nominal tensile strength of 1860 MPa (140 mm<sup>2</sup> cross sectional area) may be used in place of 15.2 mm 1830 MPa strand (143 mm<sup>2</sup> cross sectional area), with Designer approval and using the same minimum design jacking force.*

**Contact Details**

Supplier	Website	Email	Phone	Registration
				Expiry
Siam Industrial Wire (Agent: Sanwa) #	sanwa.com.au	mhorwitz@sanwa.com.au	(02) 9362 4088	1/09/2024
Silvery Dragon (Agent: United industrial) #	unitedindsupply.com	sales@unitedindsupply.com	(07) 5579 8057	31/01/2024

# Strand is only registered when supplied by the nominated agent

*Inactive: Test results to be submitted to SCM on commencement of supply*

*Suspended: May not supply to TMR projects*