

Superseded

**Specification (Measurement)**

**Transport and Main Roads Specifications  
MRS22 Supply of Cover Aggregate**

**July 2018**

Superseded

## Copyright



<http://creativecommons.org/licenses/by/3.0/au/>

© State of Queensland (Department of Transport and Main Roads) 2018

**Feedback:** Please send your feedback regarding this document to: [tmr.techdocs@tmr.qld.gov.au](mailto:tmr.techdocs@tmr.qld.gov.au)

**Contents**

- 1 Introduction .....1**
- 2 Measurement of work .....1**
  - 2.1 Standard Work Items ..... 1
  - 2.2 Work Operations ..... 1
  - 2.3 Calculation of quantities ..... 2
    - 2.3.1 *General* .....2
    - 2.3.2 *Method A – Stockpile measurement* .....3
    - 2.3.3 *Method B – Truck measurement* .....3
    - 2.3.4 *Method C – Volume measurement using weight* .....3

Superseded

## 1 Introduction

This Specification applies to the supply and delivery of cover aggregate and prime cover material for use in sprayed bituminous treatments, and the construction of stockpile sites for storage of cover aggregate.

This Specification shall be read in conjunction with MRS01 *Introduction to Specifications* and other Specifications as appropriate.

This Specification forms part of the Transport and Main Roads Specifications Manual.

## 2 Measurement of work

### 2.1 Standard Work Items

In accordance with the provisions of Clause 2.1.3 of MRS01 *Introduction to Specifications*, the Standard Work Items incorporated in this Specification are listed in Table 2.1.

**Table 2.1 – Standard Work Items**

Standard Item No.	Description	Unit of Measurement
<b>Supply of Cover Aggregate</b>		
41001	Supply of cover aggregate [ <i>precoated</i>   <i>unprecoated</i> ], [ <i>nominal size</i> ] mm nominal size	m <sup>3</sup>
41002	Supply of cover aggregate [ <i>precoated</i>   <i>unprecoated</i> ], [ <i>nominal size</i> ] mm nominal size	tonne
41003	Supply of prime cover material, [ <i>type of material</i> ]	m <sup>3</sup>
41004	Transport of materials, [ <i>type of material</i> ]	m <sup>3</sup>
41005	Construction of stockpile site	lump sum

### 2.2 Work Operations

**Item 41001** Supply of cover aggregate [*precoated* | *unprecoated*], [*nominal size*] mm nominal size

**Item 41002** Supply of cover aggregate [*precoated* | *unprecoated*], [*nominal size*] mm nominal size

Where cover aggregate is supplied and spread under the Contract, the supply of cover aggregate is typically included in Work Item 40723 “spreading cover aggregate” under MRS11 *Sprayed Bituminous Treatments (Excluding Emulsion)*. The above items should not be used in this situation.

Work Operations incorporated in the above items include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) winning and processing of the material
- c) loading, delivery and stockpiling of the cover aggregate, and
- d) precoating, if required.

**Item 41003 Supply of prime cover material, [type of material]**

Where prime cover material is supplied and spread under the Contract, the supply of prime cover material is typically included in Work Item 40722 “spreading prime cover material” under MRS11 *Sprayed Bituminous Treatments (Excluding Emulsion)*. The above item should not be used in this situation.

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) winning and processing of the material, and
- c) loading, delivery and stockpiling of the prime cover material.

**Item 41004 Transport of materials, [type of material]**

This item is to be used only where cover aggregate and / or prime cover aggregate is supplied by the Principal for collection by the Contractor at the point of supply.

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) taking delivery of cover aggregate or prime cover material at the location and by the mode nominated in the Contract, and
- c) transport to the Site and stockpiling, if required.

**Item 41005 Construction of stockpile site**

This item is to be used only for a materials supply contract. This item is not to be used where cover aggregate and / or prime cover material is supplied and spread under the Contract.

Work Operations incorporated in the above item include:

- a) Work Operations listed in Clause 2.1.5 of MRS01 *Introduction to Specifications*
- b) clearing, grubbing, compacting and trimming of the natural ground
- c) drainage of the site and the construction of access tracks
- d) construction of a pavement and a seal, where stated elsewhere in this Specification, and
- e) supply of all construction materials.

**2.3 Calculation of quantities**

**2.3.1 General**

For a material supply contract only, the quantity of cover aggregate and / or prime cover material shall be calculated by the method stated in Clause 1 of Annexure MRS22.1, which shall be one of the methods described in Clauses 2.3.2, 2.3.3 and 2.3.4.

For all other contracts, the quantity of cover aggregate and / or prime cover material shall be calculated in accordance with the method specified in Clause 2 of MRS11 *Sprayed Bituminous Treatments (Excluding Emulsion)* and / or Clause 2 of MRS12 *Sprayed Bituminous Emulsion Surfacing*, where relevant.

### 2.3.2 Method A – Stockpile measurement

The quantity of the material shall be calculated from the dimensions of the stockpile. For this purpose, the Contractor shall shape the stockpile to the requirements of Table 2.3.2.

**Table 2.3.2 – Stockpile shape requirements**

Section	Dimension
Base	Rectangular or square in plan
Height	A constant height, maximum two metres
Side slopes	Between 1.5 horizontal to 1 vertical and 2 horizontal to 1 vertical
Top Surface	Trimmed flat

### 2.3.3 Method B – Truck measurement

The quantity of material in each truck shall be calculated from the dimensions of each load. If required by the Administrator, the load shall be trimmed flat.

The total quantity of material shall be determined by the tally of the trucks and the quantity in each.

### 2.3.4 Method C – Volume measurement using weight

The total dry volume of the material shall be calculated from the tally of the masses on weighbridge docketts which represent the delivered material. Convert mass to volume by weighing a set volume.

Where necessary, as determined by the Administrator, deductions shall be made to the mass obtained from the tally of the weighbridge docketts to account for any water contained in the loads of material.

Superseded