




GENERAL ARRANGEMENT




BUSH GATE DETAIL



FIELD GATE DETAIL



GATE LOCKING DEVICE - PLAN VIEW



DETAIL A
RUNNING POST WIRE FASTENING

NOTES

1. ALL TIMBER shall be an approved hardwood as indicated in the "Road Furniture" specification.
2. FIELD GATE CHS to be grade C350 to AS 1163 and gate hinges to manufacturer's specifications.
3. WHERE HIGH TENSILE FENCING WIRE is used, every second 'Y' section post may be replaced with a hardwood dropper.
4. WIRE CONFIGURATION (wire type, number and spacing) may be varied as detailed in the Contract.
5. STAYS shall remain inline with fencing wire regardless of angle of change in horizontal alignment.
6. BOLTS, NUTS AND WASHERS to be hot-dip galvanized to AS 1214.
7. ALL STEELWORK AND FITTINGS to be hot-dip galvanized to AS/NZS 4680.
8. GALVANIZED FENCING WIRE to AS 2423.
9. DIMENSIONS are in millimetres, unless shown otherwise.

ASSOCIATED DOCUMENTS:

Department of Main Roads Manual of Standard Drawings Roads.
Department of Main Roads Manual of Standard Specifications Roads.

REFERENCED DOCUMENTS:

Standard Specifications:
Road Furniture

Australian Standards:

- AS 1163 Structural Steel Hollow Sections
- AS 1214 Hot-Dip Galvanized Coatings on Threaded Fasteners (ISO metric coarse thread series)
- AS 2423 Galvanized Wire Fencing Products
- AS/NZS 4680 Hot-Dip Galvanized (zinc) Coatings on Fabricated Ferrous Articles

1600

FENCING			
RURAL FENCE AND GATES TIMBER POSTS AND STAYS		Size A3	Drawing No
		Scales	1600
		as shown	Date 12/00
		A	