

Technical Note 45

Surface Finish of Prestressed Concrete Octagonal Piles

May 2026

Copyright

© The State of Queensland (Department of Transport and Main Roads) 2026.

Licence



This work is licensed by the State of Queensland (Department of Transport and Main Roads) under a Creative Commons Attribution (CC BY) 4.0 International licence.

CC BY licence summary statement

In essence, you are free to copy, communicate and adapt this work, as long as you attribute the work to the State of Queensland (Department of Transport and Main Roads). To view a copy of this licence, visit: <https://creativecommons.org/licenses/by/4.0/>

Translating and interpreting assistance



The Queensland Government is committed to providing accessible services to Queenslanders from all cultural and linguistic backgrounds. If you have difficulty understanding this publication and need a translator, please call the Translating and Interpreting Service (TIS National) on 13 14 50 and ask them to telephone the Queensland Department of Transport and Main Roads on 13 74 68.

Disclaimer

While every care has been taken in preparing this publication, the State of Queensland accepts no responsibility for decisions or actions taken as a result of any data, information, statement or advice, expressed or implied, contained within. To the best of our knowledge, the content was correct at the time of publishing.


Feedback

Please send your feedback regarding this document to: tmr.techdocs@tmr.qld.gov.au

1 Introduction

This document provides further guidance on the required surface finish of prestressed precast concrete piles manufactured to *MRTS73 Manufacture of Prestressed Concrete Members and Stressing Units*. A uniform Class 2 finish to AS 3610 can be difficult to achieve with the shuttered surfaces (D) of octagonal piles (see Figure 1).

Figure 1 – Surfaces of octagonal piles, as cast (E up)



2 General

MRTS73 Manufacture of Prestressed Concrete Members and Stressing Units requires:

- a) a Class 2 finish for faces A, B and C
- b) a Class 3 finish for faces D, and
- c) a steel-trowelled finish for face E.

Further to these requirements, any air (blow) holes exceeding 12 mm in lateral dimension or having a depth greater than 3 mm need to be filled. Of particular concern is the area near the pile tip which should be thoroughly checked and repaired if necessary.

3 Lower Faces

Faces 'A' 'B' and 'C' shall have a Class 2 finish to AS 3610. This should be readily achievable with clean rigid metal forms and adequate vibration of workable concrete. The slope of Face 'C' may vary up to 5 mm from the vertical to enable the pile to be easily removed from the form.

4 Inclined Faces

Precast manufacturers should also aim to achieve a Class 2 finish on faces 'D' however due to the propensity for air bubbles to become trapped in this area during vibration, a relaxation to a Class 3 is permitted.

Where the bridge design incorporates prestressed piles all the way to the headstock, this relaxation does not apply to the length of pile between ground level and the base of the headstock by default. At the Administrator's discretion, it may still be applied, for example, where aesthetics are not a concern.

5 Top Face

Face 'E' (the top face) is smooth finished with a steel trowel and then marked for length in accordance with MRTS73 *Manufacture of Prestressed Concrete Members and Stressing Units*.

6 Examples

It is recommended that sample / reference panels be kept for agreement on what constitutes a typical Class 2 and Class 3 finish. Figures 6(a) and 6(b) compare acceptable and unacceptable finishes.

Figure 6(a) – Acceptable Surface Finish following repair (Face C)



Figure 6(b) – Unacceptable surface finish (Face D)



