



NOTES:

FLOOD DEPTH INDICATORS:

1. To be located at the chainages specified or as directed by the Superintendent.
 2. Zero mark to be set at the lowest pavement level on the section of road subject to flooding.
 3. G9-22-2 and G9-22-3 indicators to be erected on progressively higher ground where flood depths are in excess of 1.5m or 3.5m respectively.
 4. To conform with the details as shown in the MUTCD.
- CONCRETE SURROUND:**
5. To be class N20/20 and provide 100mm minimum cover all round.
 6. Dimensions are in millimetres unless shown otherwise.

REFERENCED DOCUMENTS:

Departmental Specifications:
 MRTS14 Road Furniture
 MRTS70 Concrete

Australian Standards:
 AS1743 Road Signs – Specifications

ASSOCIATED DEPARTMENTAL DOCUMENTS:

Standard Drawings
 Specifications
 Manual of Uniform Traffic Control Devices Part 2 (MUTCD)

Department of Transport and Main Roads		 <small>© The State of Queensland (Department of Transport and Main Roads) 2022 http://creativecommons.org/licenses/by/4.0/</small>	
FLOOD DEPTH INDICATORS			
INSTALLATION		A3	Standard Drawing No 1170
		Not to Scale	Date 11/2022
A	B	C	D